



Connectors > Audio & Video Connectors > USB Connectors



USB Adapter Type: **A/B**

USB Version: **2.0**

Connector Profile: **Micro**

Connector & Housing Type: **Receptacle**

Number of Ports: **1**

Features

Product Type Features

Integral Locking Latch	Without
USB Adapter Type	A/B
USB Version	2.0
Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
USB Connector Type	Micro USB 2.0 Type-AB

Configuration Features

Number of Ports	1
Number of Positions	5

Body Features

Shell Plating Finish	Matte
Shell Plating Material	Tin over Nickel
Offset	0 mm



Connector Profile	Micro
-------------------	-------

Contact Features

Contact Mating Area Plating Material Thickness	.76 µm[29.52 µin]
Contact Mating Area Plating Material	Gold (Au)
Contact Current Rating (Max)	1.8 A

Termination Features

Termination Post & Tail Length	.75 mm[.03 in]
Termination Method to PCB	Surface Mount

Mechanical Attachment

Locking Feature	Without
PCB Mount Location	Top
PCB Connector Seating	Offset
PCB Mount Retention Type	Straight Leg
Panel Mount Feature Type	Flange
Connector Mounting Type	Board Mount

Housing Features

Housing Material	Thermoplastic
Housing Color	Gray
Body Orientation	Right Angle
Centerline (Pitch)	.65 mm[.025 in]

Dimensions

PCB Thickness (Recommended)	.8 – 1. mm[.031 – .039 in]
-----------------------------	----------------------------

Usage Conditions

Soldering Temperature (Max)	260 °C[500 °F]
Mating Cycles (Max)	10000
Operating Temperature Range	-30 – 85 °C[-22 – 185 °F]

Operation/Application

Halogen Free	No
Assembly Process Feature	Without Pick and Place Cover
Circuit Application	Power & Signal

Industry Standards

Industry Standard	USB 2.0
-------------------	---------



Moisture Sensitivity Level	1
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	1000
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1551629-3
MICRO USB, TYPE A/B,
SPLASHPROOF LOW MOQ

Customers Also Bought



TE Part #2-2176090-8
RP 1J 0.166W 249K 0.1% 25PPM 1K RL




TE Part #2-2176529-0
3504G 3A 80R6 1% 1K RL




TE Part #3-647166-8
8P MTA100 HDR ASSY,SM,FL,LF



TE Part #2170703-1
CAGE ASSEMBLY, QSFP28 1X1,
SPRING




TE Part #1-826634-3
13P MODU 2 PIN HDR.



TE Part #5-102975-4
08 MODII HDR DRRA B/A .100CL



TE Part #7-2176087-7
RP 1J 0.166W 432R 0.1% 25PPM 1K RL



TE Part #1546216-2
TERMI-BLOK PCB MOUNT 90 2P.



TE Part #1-1825027-1
FSMRA4JH04=R/A,TACT PB SW,160G



TE Part #7-1879225-1
CPF 0603 243K 0.1% 25PPM 1K RL

Documents

Product Drawings

MICRO USB, TYPE A/B, GRAY

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2134536-2_E2.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_2134536-2_E2.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2134536-2_E2.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[5-1773464-3_Quick_Reference_Guide_Micro_USB_Connectors](#)

English

Product Specifications

[Product Specification](#)

Japanese

[Product Specification](#)

English