TE Internal #: 2141501-2

3 Position Housing, Housing for Female Terminals, Wire-to-Wire,

3.33 mm [.131 in] Centerline, Sealable, Blue, Wire & Cable, Power

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings











Number of Positions: 3

Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: 1.5 mm [.06 in]

Connector System: Wire-to-Wire

Centerline (Pitch): 3.33 mm [.131 in]

Features

Product Type Features

Troduct Type readures	
Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Primary Locking Feature	On the Terminal
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	3
Number of Rows	1
Electrical Characteristics	
Operating Voltage	14 VAC
Nominal Voltage Architecture	14 V

180°, 90°

Body Features

Cable Exit Angle



Primary Product Color	Blue
Connector & Keying Code	2
Contact Features	
Contact Size	1.5mm
Contact Type	Receptacle
Mating Tab Width	1.5 mm[.06 in]
Contact Current Rating (Max)	16 A
Mechanical Attachment	
Strain Relief	With
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT GF
Centerline (Pitch)	3.33 mm[.131 in]
Dimensions	
Product Width	21.3 mm[.839 in]
Product Length	39.05 mm[1.535 in]
Connector Height	21 mm[.827 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C, 130 °C, 140 °C, 145 °C, 150 °C[158 °F][167 °F][176 °F] [185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F][284 °F][293 °F][302 °F]
Operating Temperature Range	-40 - 150 °C[-40 - 302 °F]
Operation/Application	
Circuit Application	Power
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







Customers Also Bought

























Documents

Product Drawings

3POS,1.5MM SFC,REC HSG,ASSY,SEALED,BU

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2141501-2_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2141501-2_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2141501-2_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

3 Position Housing, Housing for Female Terminals, Wire-to-Wire, 3.33 mm [.131 in] Centerline, Sealable, Blue, Wire & Cable, Power



Application Specification

English