




Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Receptacle**

PCB Mount Orientation: **Vertical**

Connector System: **Board-to-Board**

Number of Positions: **3**

Number of Rows: **1**

Features

Product Type Features

PCB Connector Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Stackable	Yes
PCB Mount Orientation	Vertical
Number of Positions	3
Number of Rows	1

Body Features

Connector Profile	Standard
Primary Product Color	Black

Contact Features



Mating Pin Diameter	.63 mm[.024 in]
Mating Square Post Dimension	.63 mm[.024 in]
PCB Contact Termination Area Plating Material Thickness	2.4 – 4 µm[94.488 – 157.48 µin]
Contact Shape & Form	Square
Contact Layout	Inline
Contact Protection Type	Closed Entry Housing
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin-Lead
Contact Mating Area Plating Material	Tin (Sn)
Contact Type	Receptacle
Contact Current Rating (Max)	3 A

Termination Features

Rectangular Termination Post & Tail Width	.69 mm[.027 in]
Rectangular Termination Post & Tail Thickness	.2 mm[.008 in]
Termination Post & Tail Length	3.1 mm[.122 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

PCB Mount Retention Type	Retention Solder Tails
PCB Mount Retention	With
Connector Mounting Type	Board Mount

Housing Features

Mating Entry Location	Top
Housing Material	PBT
Centerline (Pitch)	2.54 mm[.1 in]

Dimensions

PCB Thickness (Recommended)	1.6 mm[.063 in]
Connector Height	8.5 mm[.335 in]

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F][-85 – 257 °F]
-----------------------------	--

Operation/Application

Solder Process Feature	Board Standoff
------------------------	----------------

Industry Standards



UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	240
Packaging Method	Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 826937-3
3P AMPMODU II STIFT LEI

TE Part # 826947-3
03P MODU 2 PIN HDR

TE Part # 826926-3
3P AMPMODU II PIN HDR

TE Part # 966573-3
3P MOD2 ST-LEI A-P



TE Part # 826936-3
3P AMPMODU II STIFT LEI

TE Part # 826938-3
3P AMPMODU II STIFT LEI

TE Part # 826951-3
3P MOD2 STIFT LEI

TE Part # 826949-3
3P MOD2 STIFT LEI

TE Part # 826950-3
3P MOD2 STIFT LEI

Also in the Series

AMPMODU HV-100/HV-190

Board-to-Board Headers & Receptacles(321)

PCB Headers & Receptacles(321)

Customers Also Bought

TE Part #3-2176372-8
RQ 0603 121K 0.1% 10PPM 5K RL

TE Part #ANT-916-CHP-T
Antenna Chip 916MHz SMT T&R

TE Part #2-2176641-1
3627C 575047 330UH 10%

TE Part #2-2176641-2
3627C 575047 470UH 10%

TE Part #644874-3
03P MTA100 HDR ASSY,SPCL BEND

TE Part #M5600-000005-300PG
PRESS XDCR M5600-000005-300PG

TE Part #3-644044-2
02P MTA100 CONN ASSY LF

TE Part #CAT-HST-RNF100-BK
RNF-100-BK Heat Shrink Tubing



Documents

Product Drawings

3P HV100 REC CON. TE, 8.5MM,TIN

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_215300-3_G.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_215300-3_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_215300-3_G.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

1773393_ AMPMODU_EUROPEAN_STANDARD_PRODUCTS

English

Product Specifications

Product Specification

English