



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Receptacle**

PCB Mount Orientation: **Vertical**

Connector System: **Board-to-Board**

Number of Positions: **3**

Number of Rows: **2**

Features

Product Type Features

PCB Connector Type	PCB Mount Receptacle
Connector System	Board-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Stackable	Yes
PCB Mount Orientation	Vertical
Number of Positions	3
Number of Rows	2

Body Features

Connector Profile	Standard
Primary Product Color	Black



Contact Features

Mating Pin Diameter	.63 mm[.024 in]
Mating Square Post Dimension	.63 mm[.024 in]
PCB Contact Termination Area Plating Material Thickness	2.5 µm[98.42 µin]
Contact Shape & Form	Square
Contact Protection Type	Closed Entry Housing
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Socket
Contact Current Rating (Max)	3 A

Termination Features

Rectangular Termination Post & Tail Width	.69 mm[.027 in]
Rectangular Termination Post & Tail Thickness	.2 mm[.008 in]
Termination Post & Tail Length	3.1 mm[.122 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

PCB Mount Retention Type	Retention Solder Tails
PCB Mount Retention	With
Connector Mounting Type	Board Mount

Housing Features

Mating Entry Location	Top
Housing Material	Polyester GF
Centerline (Pitch)	2.54 mm[.1 in]

Dimensions

Row-to-Row Spacing	2.54 mm[.1 in]
PCB Thickness (Recommended)	1.6 mm[.063 in]
Connector Height	7 mm[.276 in]

Usage Conditions

Operating Temperature Range	-65 – 125 °C[-67 – 221 °F][-85 – 257 °F]
-----------------------------	--

Operation/Application

Solder Process Feature	Board Standoff
------------------------	----------------



Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	240
Packaging Method	Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



TE Part # 966269-3
2x3P MOD II BREAK AWAY HDR,SMD,
TUBE PKG



TE Part # 966709-3
2X3P MODUII BREAK AWAY HEADER,
SMD




TE Part # 826632-3
3P AMPMODU II PIN HDR.



TE Part # 829394-3
2X3P MOD II UNSHRD HDR, ST, 0.8 AU



TE Part # 1241050-3
2x3P MOD II BREAK AWAY HDR,SMD,
BLISTER



TE Part # 215447-3
2X 3P MOD2 STIFTLEI



TE Part # 826664-3
3P MOD2 STIFT LEI



TE Part # 826662-3
3P AMPMODU II STIFT LEI



TE Part # 826634-3
AMPMODU MOD II PIN HEADER




TE Part # 826656-3
3P AMPMODU II STIFT LEI




TE Part # 826658-3
3P AMPMODU II STIFT LEI

Also in the Series | [AMPMODU HV-100/HV-190](#)



Board-to-Board Headers &
Receptacles(321)



PCB Headers & Receptacles(321)

Customers Also Bought



TE Part #521408-2
ULTRA-POD 110 ASSY REC 22-18
AWG TPBR



TE Part #ANT-868-CW-HW-SMA
Antenna 1/2 Wave Whip 868MHz SMA




TE Part #2-2213766-7
AV19 SPL 3A POWER LED RED 24V



TE Part #2118308-3
4G WORLD BAND, METASPAN, PCB
ANT, 150MM




TE Part #2199155-1
DDR4 DIMM 288 Pin SMT type




TE Part #282856-2
TERMI-BLOK PCB MOUNT 2P



TE Part #826656-7
7P AMPMODU II STIFT LEI



TE Part #215307-6
2X6P HV100 REC CON. TE, 7.0MM



TE Part #215307-8
2X8P HV100 REC CON. TE, 7.0MM



TE Part #ANT-868-CW-QW-SMA
Antenna 1/4 Wave Whip 868MHz SMA

Documents

Product Drawings

2X3P HV100 REC CON. TE, 7.0MM

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_215307-3_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_215307-3_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_215307-3_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Product Specification

English