TE Internal #: 2170680-5

SFP+, Cage Assembly, Sealable, Signal, Operating Temperature

Range -55 – 105 °C [-67 – 221 °F], Data Rate (Max) 16 Gb/s, 1 Ports

View on TE.com >




Connectors > Pluggable IO Connectors & Cages











Form Factor: **SFP+**

Pluggable I/O Product Type: Cage Assembly

Sealable: Yes

Circuit Application: Signal

Operating Temperature Range: -55 – 105 °C [-67 – 221 °F]

Features

Product Type Features

Cage Type	Single
Form Factor	SFP+
Pluggable I/O Product Type	Cage Assembly
Sealable	Yes
Configuration Features	
Number of Ports	1
Port Matrix Configuration	1 × 1
Electrical Characteristics	
Data Rate (Max)	16 Gb/s

Termination Features

Usage Conditions

On a wating of Tamana a water was Danaga	FF 10F 0C[/7 221 0F]
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Operation/Application



Pluggable I/O Applications	SFP+
Heat Sink Compatible	No
Circuit Application	Signal
Packaging Features	
Packaging Method	Reel
Other	
Included Lightpipe	No
EMI Containment Feature Type	Internal/External EMI Springs

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # 2821033-8 QSFP TO [4]SFP+, 28G, 1M, 33AWG



TE Part # 4-2334985-2 SFP56 DIRECT ATTACH CA, 1M, 32AWG



TE Part # 2334985-2 SFP28 DIRECT ATTACH CA, 1M, 32AWG



TE Part # CAT-C11-N49011 SFP28 to SFP28 Cable Assembly: 26 AWG



TE Part # 4-2821224-5 SFP56 DIRECT ATTACH CA, 3M, 26AWG



TE Part # CAT-Q17-N49011

QSFP56-Four SFP56 Cable Assembly:
30 AWG



TE Part # CAT-C11-N490333

QSFP28-Four SFP+ Cable Assembly:
30 AWG



TE Part # CAT-C11-N490325 QSFP28-Four SFP+ Cable Assembly: 26 AWG



TE Part # CAT-Q17-N490333 QSFP56-Four SFP56 Cable Assembly: 26 AWG



TE Part # 4-2821222-5 SFP56 DIRECT ATTACH CA, 2M, 30AWG



TE Part # CAT-C11-N4901114 SFP28 to SFP28 Cable Assembly: 30 AWG

Customers Also Bought





TE Part #1551012-1 Vert.Male, Telcordia L3



QSFP28, 1X2, CAGE ASSY, SPRING,

HS, LP

Documents

CAD Files

EXTENDED

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2170680-5_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2170680-5_A.3d_igs.zip

English

SFP+, Cage Assembly, Sealable, Signal, Operating Temperature Range -55 – 105 °C [-67 – 221 °F], Data Rate (Max) 16 Gb/s, 1 Ports



Customer View Model

ENG_CVM_CVM_2170680-5_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English