

Holsworthy | Holsworthy UPF

TE Internal #: 2176163-9 20 ohm, Through-Hole Precision Resistor, Metal Film, .5 W, .1 %, ±5 ppm/°C, Axial-Leaded, Copper Termination, 10.2 x 4 mm, Bulk, Holsworthy UPF

View on TE.com >



Passive Components > Resistors > Through-Hole Resistors



Resistance Value: 20Ω

Resistor Type: Precision Resistor

Element Type: Metal Film

Power Rating: .5 W

Resistance Class: Up to $1k\Omega$

Features

Product Type Features

Resistor Type

Element Type

Precision Resistor

Metal Film

Configuration Features

Number of Resistors	1	
Electrical Characteristics		

Operating Voltage	300 V
Resistance Value	20 Ω
Power Rating	.5 W
Resistance Class	Up to 1kΩ
Passive Component Tolerance	.1 %
Body Features	
Lead Type	Axial-Leaded
Termination Features	
Termination Area Base Material	Copper
Number of Terminations	2
Dimensions	
Passive Component Dimensions	10.2 x 4 mm

C For support call+1 800 522 6752

UPF50B20RV

20 ohm, Through-Hole Precision Resistor, Metal Film, .5 W, .1 %, ±5 ppm/°C, Axial-Leaded, Copper Termination, 10.2 x 4 mm, Bulk, Holsworthy UPF



Usage Conditions

Operating Temperature Range	-55 – 125 °C
Temperature Coefficient	±5 ppm/°C
Packaging Features	
Packaging Method	Bulk
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

UPF50B20RV


20 ohm, Through-Hole Precision Resistor, Metal Film, .5 W, .1 %, ±5 ppm/°C, Axial-Leaded, Copper Termination, 10.2 x 4 mm, Bulk, Holsworthy UPF








Also in the Series | Holsworthy UPF





Customers Also Bought



UPF50B20RV

20 ohm, Through-Hole Precision Resistor, Metal Film, .5 W, .1 %, ±5 ppm/°C, Axial-Leaded, Copper Termination, 10.2 x 4 mm, Bulk, Holsworthy UPF



TE Part #CUA480F53440050000 940 PLUG, ANGLED

Documents

Product Drawings UPF50 0.1% 5PPM 20R

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2176163-9_BA.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2176163-9_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2176163-9_BA.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages High Precision Metal Film Leaded Resistor Type UPF Series

English