

#### **CROWN CLIP**

TE Internal #: 2178411-1

Board-to-Bus Bar, 1 Position, Printed Circuit Board, Thermoplastic, Black, Swage Mount, Tray, Right Angle, Vertical, Copper Alloy,

**Busbar Connectors** 

View on TE.com >



Connectors > Power Connectors > Busbar Connectors











Connector System: Board-to-Bus Bar

Number of Positions: 1

Connector & Contact Terminates To: Printed Circuit Board

Mating Conductor Thickness: 3 mm [.118 in]

Housing Material: Thermoplastic

## **Features**

## **Product Type Features**

Connector & Housing Type	Receptacle
Connector System	Board-to-Bus Bar
Connector & Contact Terminates To	Printed Circuit Board

## **Configuration Features**

Number of Positions	1
PCB Mount Orientation	Right Angle
Mating & Unmating Configuration	Hot Pluggable

## **Body Features**

Bus Bar Contact Plating Material	Tin
----------------------------------	-----

## **Contact Features**

Contact Base Material	Copper Alloy
Contact Current Rating (Max)	170 A
Contact Length	28.1 mm[1.106 in]
Bus Bar Contact Style	Socket



#### **Termination Features**

Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Mating Alignment	Without
Bus Bar Connector Mounting Retention	Without
PCB Mount Retention Type	Retention Solder Tails
Bus Bar Mount Retention Type	Swage Mount
Bus Bar Mount Orientation	Vertical
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Thermoplastic
Housing Color	Black
Usage Conditions	
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]
Operation/Application	
Circuit Application	Power
Packaging Features	
Packaging Method	Tray
Other	
Mating Conductor Thickness	3 mm[.118 in]

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free



#### Solder Process Capability

Wave solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



# Customers Also Bought























#### **Documents**

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2178411-1\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2178411-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2178411-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

## Datasheets & Catalog Pages

**Busbar Power Brochure** 

English

## Agency Approvals

**UL Report** 

English