Mini-SAS HD

TE Internal #: 2198483-1

TE Internal Description: MiniSAS HD 1x2 Rec Assy w/ LP

Mini-SAS HD Cages

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > Mini-SAS HD Cages











Form Factor: Mini-SAS HD

Pluggable I/O Product Type: Receptacle Assembly

Centerline (Pitch): .03 mm [.75 in]

Circuit Application: Signal

Operating Temperature Range: -55 - 85 °C [-67 - 185 °F]

All Mini-SAS HD Cages (11)

Features

Product Type Features

Termination Features

Termination Method to PCB

Termination Post & Tail Length

Product Type Features	
Form Factor	Mini-SAS HD
Pluggable I/O Product Type	Receptacle Assembly
Configuration Features	
Number of Positions	72
Number of Ports	2
Port Matrix Configuration	1 x 2
Electrical Characteristics	
Data Rate (Max)	12 Gb/s
Contact Features	
Contact Base Material	Copper Alloy

Through Hole - Press-Fit

1.64 mm[.065 in]



Housing Features

Housing Material	LCP
Centerline (Pitch)	.03 mm[.75 in]

Dimensions

PCB Thickness (Recommended)	.97 mm[.038 in]
Profile Height from PCB	16.44 mm[.647 in]

Usage Conditions

Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]

Operation/Application

Circuit Application	Signal	
---------------------	--------	--

Industry Standards

Packaging Features

Packaging Method	Box & Tray	
	2 37. 3	

Other

Included Lightpipe	Yes
EMI Containment Feature Type	Internal/External EMI Springs

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Also in the Series | Mini-SAS HD







Customers Also Bought





Documents

Product Drawings

MiniSAS HD 1x2 Rec Assy w/ LP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2198483-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2198483-1_B.3d_igs.zip

English



Customer View Model

ENG_CVM_CVM_2198483-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

7-1773461-9_MINI_SAS_HD_INTERCONNECT

English

Product Specifications

Application Specification

English

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL Report

English