TE Internal #: 2227303-1


SFP, Cage, Operating Temperature Range -55 – 85 °C [-67 – 185 °

F], Data Rate (Max) 4 Gb/s, 1 Ports, Port Matrix Configuration 1 x 1

View on TE.com >





#### Connectors > Pluggable IO Connectors & Cages











Form Factor: **SFP** 

Pluggable I/O Product Type: Cage

Sealable: No

Operating Temperature Range: -55 - 85 °C [ -67 - 185 °F ]

Data Rate (Max): 4 Gb/s

## **Features**

# **Product Type Features**

Cage Type	Single
Form Factor	SFP
Pluggable I/O Product Type	Cage
Sealable	No

## **Configuration Features**

Number of Ports	1
Port Matrix Configuration	1 x 1

#### **Electrical Characteristics**

Data Rate (Max)	4 Gb/s
Data Nate (Max)	1 00/3

### **Contact Features**

T 11 51	<del></del> .	
Tail Plating Material	lin	

### **Termination Features**

Termination Method to PCB	Through Hole - Solder
Termination Post & Tail Length	3.56 mm[.14 in]

## **Housing Features**



Cage Material	Stainless Steel
Dimensions	
PCB Thickness (Recommended)	1.5 mm[.059 in]
Usage Conditions	
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
Operation/Application	
Pluggable I/O Applications	zSFP+ Thermally Enhanced
Heat Sink Compatible	No
Packaging Features	
Packaging Method	Tray
Other	
Included Lightpipe	No
EMI Containment Feature Type	Internal/External EMI Springs

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



DUST COVER, SFP, GANGED & STACKED



TE Part # 1367147-3
SFP COVER, UNPL, NO LOGO



TE Part # 1367147-1 SFP COVER, UNPLATED



TE Part # 1888901-1 SFP+ EMI Plug



# Customers Also Bought



TE Part #1735610-1 ASSY, SAS PLUG, SMT, 15+7+7P



TE Part #2327678-9 RECEPTACLE ASSY, 84 P, VERT, SLIVER 2.0



TE Part #5353999-2 0.8FH,R05H.5,060,30/Sn,TR,SC



TE Part #8-5353159-0
ON TAPING (EMBOSS) 0.5MM PITCH








TE Part #1-2322024-9

MBXL VERT HDR STR 6LP + 52S + 4LP







## **Documents**

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_2227303-1\_C1.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2227303-1\_C1.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2227303-1\_C1.3d\_igs.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

## **Product Specifications**

**Application Specification** 

English