

AMP | LEAVYSEAL

TE Internal #: 2236721-1

Black, PBT GF, Alignment Plate, -40 – 120 °C [-40 – 248 °F],

LEAVYSEAL

View on TE.com >



Connectors > Automotive Connector > Automotive Connector Accessories > Other Automotive Connector Accessories > LEAVYSEAL Mounting Accessories











Primary Product Color: Black

Primary Product Material: PBT GF

Automotive Connector Accessory Type: Alignment Plate

Operating Temperature Range: -40 - 120 °C [-40 - 248 °F]

All LEAVYSEAL Mounting Accessories (8)

Features

Product Type Features

Automotive Connector Accessory Type	Alignment Plate	
Configuration Features		
Number of Positions	39, 62	
Body Features		
Primary Product Color	Black	
Primary Product Material	PBT GF	
Usage Conditions		
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]	
Industry Standards		
UL Flammability Rating	UL 94HB	
Packaging Features		
Packaging Method	Box	



Packaging Quantity 120

Other

Serviceable	Yes	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts








Also in the Series | LEAVYSEAL





Automotive Connector Caps & Covers




Automotive Connector Locks & Position Assurance(4)



Automotive Housings(117)





Rectangular Power Connectors(12)

Customers Also Bought



TE Part #1703810-6 SLIDE, TAB HSG GROUP B



TE Part #CAT-L489-M8649 LEAVYSEAL Mounting Accessories



TE Part #1-1718324-1 1.5/2.8MM TAB HSG.,62POS.,ASSY



TE Part #2112166-1 SLIDE,FOR 21POS.



LEAVYSEAL

TE Part #K1157198-4 Toggle Switch 07-2-2-10 939 CV750

TE Part #K1152994-4 Emergency Stop Switch ES-2012-T111 CV750

TE Part #K1023449 Relay 75A 12V*S-FL*LK*B 29-031-11B-

TE Part #K1143682-4 Push button switch TS-211-GN12 CV750

Documents



Product Drawings

ADAPTER, FOR TAB HOUSING, ASSY

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2236721-1_A_c-2236721-1-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2236721-1_A_c-2236721-1-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2236721-1_A_c-2236721-1-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

LEAVYSEAL CONNECTORS

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English