TE Internal #: 2294408-1

zSFP+, Cage Assembly, Signal, Operating Temperature Range -40

- 85 °C [-40 − 185 °F], Data Rate (Max) 32 Gb/s, 8 Ports

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > zSFP+ Cage Assembly: EMI Springs



Form Factor: **zSFP+**

Pluggable I/O Product Type: Cage Assembly

Sealable: No

Circuit Application: Signal

Operating Temperature Range: -40 - 85 °C [-40 - 185 °F]

All zSFP+ Cage Assembly: EMI Springs (24)

Features

Product Type Features

Cage Type	Ganged
Thermal Accessory Type Included	Heat Sink
Form Factor	zSFP+
Pluggable I/O Product Type	Cage Assembly
Sealable	No

Configuration Features

Lightpipe Style	Standard
Number of Ports	8
Port Matrix Configuration	1 x 8

Electrical Characteristics

Data Rate (Max)	32 Gb/s	

Body Features

Heat Sink Style	Pin
Heat Sink Finish	Electroless Nickel
	.358 in
Heat Sink Height Class	Networking Short

Termination Features



Termination Method to PCB	Through Hole - Press-Fit
Termination Post & Tail Length	2.05 mm[.081 in]
Housing Features	
Cage Material	Nickel Silver Alloy
Dimensions	
PCB Thickness (Recommended)	2.25 mm[.089 in]
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Heat Sink Compatible	Yes
Circuit Application	Signal
Packaging Features	
Packaging Method	Tray
Other	
Included Lightpipe	Yes

Product Compliance

EMI Containment Feature Type

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Internal/External EMI Springs

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2215068-4
ASSY, SEATING TOOL 1X8 LP, HS



TE Part # CAT-C11-N490111 SFP28 to SFP28 Cable Assembly: 28 AWG



TE Part # CAT-C11-N4901114 SFP28 to SFP28 Cable Assembly: 30 AWG



TE Part # 4-2821222-5
SFP56 DIRECT ATTACH CA, 2M,
30AWG



TE Part # 2334985-2 SFP28 DIRECT ATTACH CA, 1M, 32AWG



TE Part # CAT-C11-N49011 SFP28 to SFP28 Cable Assembly: 26 AWG



TE Part # 4-2821224-5 SFP56 DIRECT ATTACH CA, 3M, 26AWG



TE Part # CAT-Q17-N49011

QSFP56-Four SFP56 Cable Assembly:
30 AWG



TE Part # CAT-C11-N490333

QSFP28-Four SFP+ Cable Assembly:
30 AWG



TE Part # CAT-C11-N490325 QSFP28-Four SFP+ Cable Assembly: 26 AWG



TE Part # CAT-Q17-N490333

QSFP56-Four SFP56 Cable Assembly:
26 AWG



TE Part # 4-2334985-2 SFP56 DIRECT ATTACH CA, 1M, 32AWG

Customers Also Bought













TE Part #5-2301994-8 RJ45 JACK INT.MAG. 10/100 LED 1X1 INV.









Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2294408-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2294408-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2294408-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

zSFP+ Interconnect Brochure

English