

TE Internal #: 2332676-2

SMPM Connector, Jack, 50 ohm, Push-On, 0 – 40 GHz, Cable-to-Board, 1 Position, Wire & Cable, Panel Mount, -55 – 105 °C [-67 –

221 °F], Solder

View on TE.com >



Connectors > RF Connectors > Coax Connectors











RF Interface: **SMPM**

RF Connector Style: Jack

Impedance: 50Ω

Compatible With RF Cable Type: .047 Semi-Rigid or Flex

RF Connector Coupling Mechanism: Push-On

Features

Product Type Features

Connector Product Type	Connector Assembly
RF Interface	SMPM
RF Connector Style	Jack
Compatible With RF Cable Type	.047 Semi-Rigid or Flex
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	1
Number of Coaxial Contacts	1
Electrical Characteristics	
Impedance	50 Ω
Impedance Body Features	50 Ω



Body Material	Beryllium Copper
Body Material Finish	Plated
Body Plating Material	Gold
Contact Features	
RF Connector Center Contact Underplating Material	Nickel
RF Connector Center Contact Plating Material	Gold (Au)
RF Connector Center Contact Material	Beryllium Copper
Termination Features	
Termination Method to Wire & Cable	Solder
Mechanical Attachment	
RF Connector Coupling Mechanism	Push-On
Connector Mounting Type	Panel Mount
RF Contact Captivation Method	Mechanical
Detent	Without
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Signal
Operating Frequency	0 – 40 GHz
Packaging Features	
Packaging Method	Package
Other	
Dielectric Material	PTFE

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247)



SVHC > Threshold:

Pb (.6% in 74020097)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Low Bromine/Chlorine - Br and Cl < 900

ppm per homogenous material. Also BFR

/CFR/PVC Free

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts























Customers Also Bought









Documents

Product Drawings

SMPM CABLE JACK VITA 67-3 SNAP 047

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2332676-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2332676-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2332676-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English