

DEUTSCH | DEUTSCH NTSEAL

TE Internal #: 2350890-1

20 Position Housing, Housing for Female Terminals, Wire-to-Wire,

3.5 mm [.138 in] Centerline, Sealable, Black, Wire & Cable, Power,

DEUTSCH NTSEAL

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings











Number of Positions: 20

Connector & Housing Type: Housing for Female Terminals

Mating Pin Diameter: 1 mm, 1.55 mm [.039 in, .061 in]

Connector System: Wire-to-Wire
Centerline (Pitch): 3.5 mm [.138 in]

Features

Product Type Features

Product Type Features	
Connector Shape	Rectangular
Mixed & Hybrid Connector	Yes
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	20
Number of Rows	5
Body Features	

Black

А

Primary Product Color

Connector & Keying Code



Contact Size	Size 16, Size 20
Contact Type	Receptacle
Mating Pin Diameter	1 mm, 1.55 mm[.039 in][.061 in]
Contact Current Rating (Max)	13 A
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	3.5 mm[.138 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]
Operation/Application	
Circuit Application	Power

Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

Connector Position Assurance Capable

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Octamethylcyclotetrasiloxane (D4) (.5% in Component Part) Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part) Decamethylcyclopentasiloxane (D5) (.5% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.



Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2350891-1 20POS,HYBRID,PIN HSG ASSY,SLD, COD A



TE Part # 2357302-2 BACKSHELL,CONN KIT



TE Part # 1-2350891-1 20POS,HYBRID,PIN HSG ASSY,SLD, COD A



TE Part # 2-2350891-1 20POS,HYBRID,PIN HSG ASSY,SLD, COD A













Also in the Series | DEUTSCH NTSEAL











Customers Also Bought






















Documents

Product Drawings

20POS,HYBRID,SOC HSG ASSY,SLD,COD A

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2350890-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2350890-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2350890-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use



Datasheets & Catalog Pages

NTSEAL Sealed Wire-to-Wire Connectors

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English