



Connectors > Modular Jacks & Plugs > RJ45 Connectors



Modular Jack & Plug Interface Type: **RJ45**

Port Configuration: **Single Port**

Port Matrix Configuration: **1 x 1**

Modular Jacks & Plugs Products: **RJ Type Jacks & Plugs**

Connector Contact Density: **Standard**

Features

Product Type Features

Connector Product Type	Connector Assembly
Modular Jack & Plug Interface Type	RJ45
Modular Jacks & Plugs Products	RJ Type Jacks & Plugs
Modular Connector Style	Plug
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Multiple Port Configuration	Stacked
Port Configuration	Single Port
Port Matrix Configuration	1 x 1
Connector Contact Density	Standard
Number of Positions	8
Number of Loaded Positions	4

Signal Characteristics

Data Rate	1000 Mb/s
-----------	-----------



Body Features

Insulator Material	Polymer
Shield Plating Material	Nickel
Shield Plating Finish	Matte
Shield Material	Copper Zinc Alloy
Connector Profile	Standard

Contact Features

Contact Underplating Material	Nickel
Contact Current Rating (Max)	1.5 A
Contact Mating Area Plating Material	Gold (Au)
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material Thickness	.76 µm

Housing Features

Centerline (Pitch)	1.02 mm
Housing Color	Orange
Housing Material	Polyamide

Dimensions

Connector Height	16.5 mm
------------------	---------

Usage Conditions

Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
-----------------------------	---------------------------

Operation/Application

Indicator Type	No Indicator
Shielded	Yes
Circuit Application	Power & Signal

Industry Standards

IP Rating	IP20
UL Flammability Rating	UL 94V-0
Performance Category	Cat 5e

Packaging Features

Packaging Quantity	1
Packaging Method	Box



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: UV-329 (1% in 16619254092) Article Safe Usage Statements: Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 203318-E
MJIM IM 1X1 S 810 GF5 X R THRU * L1A M6A



TE Part # 203533-E
MJ ES R L2 8 8 * * GF5 R * 30 * J 3 2035











TE Part # 203319-E
MJIM IM 1X1 S 810 GF5 X R THRU * L2A M6A




TE Part # 133268-E
MJ LS * * 8 8 * * * * 30 * J 3 133854



 TE Part # 203497-E MJIM IMV 1X1 S 88 * X R THRU * L1 M3F01	 TE Part # 203537-E MJ ES R L5 8 8 ** GF5 R * 30 * J 3 2035	 TE Part # 203546-E MJIM IM 1X1 S 87 * X R THRU ** H3D01 *	 TE Part # 203512-E MJ HS V5 * 8 8 **** 999999 30 * J 3 1 H3D01 *
 TE Part # 203535-E MJ ES R L8 8 ** GF5 R * 30 * J 3 2035	 TE Part # 133051-E MJ DS-LG5 ** 8 8 2 **** 30 * J 3 133	 TE Part # 133041-E MJ DS-LG5 ** 8 8 4 * GF9 ** 30 * J 3 1	 TE Part # 133167-E MJ HS R51 * 8 8 ** GF5 ** 30 5 J 3 133
 TE Part # 133921-E MJ HS G5 * 8 8 2B * GF5 ** 30 5 J 3 133	 TE Part # 133044-E MJ DS-LG5 ** 8 8 8 **** 30 * J 3 133	 TE Part # 203530-E MJ ES R * 8 8 ** GF5 R * 30 * J 3 20352	 TE Part # 203441-E MJ LSS ** 8 8 ** GF5 STP 999999 30 * J
 TE Part # 203544-E MJIM IM 1X2 S 88 GF5 T R THRU * L2 H3D01	 TE Part # 203532-E MJ ES R L1 8 8 ** GF5 R * 30 * J 3 2035	 TE Part # 203323-E MJIM IMV 1X1 S 88 * X R THRU * L1 M3D01	 TE Part # 203422-E MJ LSS ** 8 8 *** STP GURT 30 * J 3 2

Customers Also Bought

 TE Part #1676317-2 RN 0805 37K4 0.1% 10PPM 1KRL	 TE Part #1676164-2 RN 0805 11K8 0.1% 10PPM 1KRL	 TE Part #1676281-2 RN 0805 2K05 0.1% 10PPM 1KRL	 TE Part #1060984-1 5862 5002 09,OSX PCB JACK
--	--	--	---



TE Part #1337808-1
50 OHM COAX SMA STR PLUG STR P

TE Part #6-1676913-9
YR1 0.1% 2K1

TE Part #1SNA179534R2200
BRT80A

TE Part #M3031-000005-100PG
PRESS XDCR M3031-000005-100PG

TE Part #1614906-2
CPF0805 20K 0.1% 25PPM 5K RL

TE Part #6-1676913-6
YR1 0.1% 29K4

Documents

Product Drawings

RJ45 FIELD INSTALLABLE CABLE CONN.

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2383216-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2383216-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2383216-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (non U.S.)

English

Agency Approvals

UL

2383216-1

RJ45 Connector, Single Port, 1 x 1, Plug, Shielded, Cat 5e, 8 Position, Standard Profile, 1.02 mm Centerline, Wire & Cable, Power & Signal, Orange



English