

AMP-IN

TE Internal #: 2393199-1 Receptacle, 1.8 – 1.9 mm [.071 – .075 in] PCB Hole, 22 – 18 AWG, . 341 – .846 mm² Wire, Through Hole - Solder, Tin Plating, Reel, PCB Terminals

View on TE.com >

Terminals & Splices > PCB Terminals



PCB Terminal Type: Receptacle

PCB Thickness (Recommended): 1.6 mm [.063 in]

PCB Hole Diameter: 1.8 – 1.9 mm [.071 – .075 in]

Profile Height from PCB: 3.5 mm [.138 in]

Compatible Insulation Diameter (Max): **3 mm [.118 in]**

Features



Product Type Features

Terminal Features	Stud Hole						
Contact Features							
Contact Underplating Material Thickness	.5 μm[19.68 μin]						
Contact Mating Area Plating Material Thickness	.8 μm[31.5 μin]						
PCB Terminal Type	Receptacle						
Terminal Plating Material	Tin						
Contact Underplating Material	Brass						
Terminal Size	Miniature						
Terminal Orientation	Straight						
Termination Features							
Termination Method to PCB	Through Hole - Solder						
Product Terminates To	Printed Circuit Board						
Dimensions							
Extension Below Board	2.35 mm[.093 in]						

C For support call+1 800 522 6752

2393199-1

Receptacle, 1.8 – 1.9 mm [.071 – .075 in] PCB Hole, 22 – 18 AWG, .341 – .846 mm² Wire, Through Hole - Solder, Tin Plating, Reel, PCB Terminals



PCB Thickness (Recommended)	1.6 mm[.063 in]
PCB Hole Diameter	1.8 – 1.9 mm[.071 – .075 in]
Profile Height from PCB	3.5 mm[.138 in]
Compatible Insulation Diameter (Max)	3 mm[.118 in]
Compatible Insulation Diameter Range	1.5 – 3. mm[.059 – .118 in]
Wire Size	.341 – .846 mm²
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
ndustry Standards	
Compatible With Agency/Standards Products	UL
Packaging Features	
Packaging Method	Reel
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

2393199-1

Receptacle, 1.8 – 1.9 mm [.071 – .075 in] PCB Hole, 22 – 18 AWG, .341 – .846 mm² Wire, Through Hole - Solder, Tin Plating, Reel, PCB Terminals



Compatible Parts



KIT REPRESENTATION

TE Part # 7-2398990-7 OCEAN_2.0_SPARE_PART_KIT-055F130F



TE Part # 2398990-1 OCEAN_2.0_APPLICATOR-S-055F130F-RSM



TE Part # 2398990-2 OCEAN_2.0_APPLICATOR-S-055F130F-RSA

Customers Also Bought







TE Part #2408288-2 CA. DUAL RAPID LOCK 5.7MM, 5X10AWG, 536MM	TE Part #2373026-1 CA, CCJ TO 3*Dynamic	

Documents

Product Drawings

MINI AMP-IN BOARD IN CONTACT, 22-18AWG

English

CAD Files

Customer View Model

2393199-1

Receptacle, 1.8 – 1.9 mm [.071 – .075 in] PCB Hole, 22 – 18 AWG, .341 – .846 mm² Wire, Through Hole - Solder, Tin Plating, Reel, PCB Terminals



ENG_CVM_CVM_2393199-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2393199-1_A.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_2393199-1_A.3d_igs.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English