




Connectors > RF Connectors > Coax Connectors



RF Interface: **SMA**

RF Connector Style: **Jack**

Impedance: **50 Ω**

RF Connector Coupling Mechanism: **Screw**

Operating Frequency: **0 – 18 GHz**

Features

Product Type Features

RF Interface	SMA
RF Connector Style	Jack
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

PCB Mount Orientation	Vertical
Number of Positions	1
Number of Coaxial Contacts	1

Electrical Characteristics

Impedance	50 Ω
-----------	------

Body Features

Body Underplating Material	Nickel
Body Material	Brass
Body Material Finish	Plated



Body Plating Material	Gold
-----------------------	------

Contact Features

RF Connector Contact Configuration	Captivated Contacts
RF Connector Center Contact Underplating Material	Nickel
	30 µin
RF Connector Center Contact Plating Material	Gold (Au)
RF Connector Center Contact Material	Beryllium Copper

Termination Features

Termination Method to PCB	Through Hole - Solder
---------------------------	-----------------------

Mechanical Attachment

Panel Attachment Style	Rear Mount
RF Connector Coupling Mechanism	Screw
Connector Mounting Type	Board Mount
RF Contact Captivation Method	Mechanical

Usage Conditions

Operating Temperature Range	-65 – 165 °C[-85 – 329 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Signal
Operating Frequency	0 – 18 GHz

Packaging Features

Packaging Quantity	100
Packaging Method	Bag

Other

Lockwasher Material	Brass
Dielectric Material	Polytetrafluoroethylene (PTFE)

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	





Current ECHA Candidate List: JAN 2025  
(247)  
Candidate List Declared Against: JAN 2025  
(247)  
SVHC > Threshold:  
Pb (4% in Component Part)  
**Article Safe Usage Statements:**  
Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE’s information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) ‘Guidance on requirements for substances in articles’(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of ‘complex object’, the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA “Guidance on requirements for substances in articles” (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts


 <div>TE Part # 2477465-1 SMA Plug to SMA Plug RA 18 GHz SUS</div>	 <div>TE Part # CSA-SMAM-216-RSFB SMA to RP-SMA 216mm RG174</div>	 <div>TE Part # CONSMA012 SMA RA Plug 50 Ohm Cable Crimp</div>	 <div>TE Part # CSD-SMAM-610-NM SMA to SMA 610mm RG58</div>
 <div>TE Part # 2486504-1 SMA Plug RA Direct Solder RG-142/U SUS</div>	 <div>TE Part # CONSMA007 SMA Plug 50 Ohm Cable Crimp</div>	 <div>TE Part # 2466282-1 SMA PLUG STR SOLDER .085 .086 18 GHZ SUS</div>	 <div>TE Part # CSE-SGAM-305-SGAM SMA to SMA 305mm RG316</div>




Customers Also Bought




TE Part #1SNG607010R0000  
EP-LN-M25-LGR-A




TE Part #1-1761608-5  
IDC LOW PRO HDR 50P VERT SHT L




TE Part #2484780-1  
SMA Jack Str SMD Pin Thru Hole 18 GHz




TE Part #8-1879127-8  
RN 0402 499R 0.1% 10PPM CUT LENGTH




TE Part #ZPF000000000109241  
DBAS 70-37-3 SN 059




TE Part #2483396-1  
BNC M to HDBNC M Str 75 Ohm NFC55a 6 in




TE Part #2-2308350-8  
CRIMP BARREL18



TE Part #ZPF000000000012647  
DBAS 70-37-3 PN



TE Part #2446052-1  
HDBNC PLUG,75OHM,CRIMP, 1855A CABLE,12G



TE Part #2446155-1  
HIGH D BNC,RA JK 50OHM,BKD,PCB, 12GHZ

Documents

Product Drawings

SMA Jack Str PCB Thru Hole BHD 18 GHz

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_2484639-1\_1.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_2484639-1\_1.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_2484639-1\_1.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.



Datasheets & Catalog Pages

[rf-connectors-product-extension-flyer-en](#)

English

[test-probe-connector-en-flyer](#)

English

---

Product Specifications

[Product Specification](#)

English