



TE Internal #: 2484640-1

SMP Connector, Plug, 50 ohm, Push-On, 0 – 18 GHz, Cable-to-Board, 1 Position, Printed Circuit Board, Board Mount, -40 – 125 °C [-40 – 257 °F]

[View on TE.com >](#)

Connectors > RF Connectors > Coax Connectors



RF Interface: **SMP**

RF Connector Style: **Plug**

Impedance: **50 Ω**

RF Connector Coupling Mechanism: **Push-On**

Operating Frequency: **0 – 18 GHz**

Features

Product Type Features

RF Interface	SMP
RF Connector Style	Plug
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

PCB Mount Orientation	Vertical
Number of Positions	1
Number of Coaxial Contacts	1

Electrical Characteristics

Impedance	50 Ω
-----------	------

Body Features

Body Underplating Material	Nickel
Body Material	Beryllium Copper



Body Material Finish	Plated
Body Plating Material	Gold

Contact Features

RF Connector Contact Configuration	Captivated Contacts
RF Connector Center Contact Plating Material	Gold (Au)
RF Connector Center Contact Material	Beryllium Copper

Termination Features

Termination Method to PCB	Surface Mount
---------------------------	---------------

Mechanical Attachment

RF Connector Coupling Mechanism	Push-On
Connector Mounting Type	Board Mount
RF Contact Captivation Method	Mechanical

Usage Conditions

Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Signal
Operating Frequency	0 – 18 GHz

Packaging Features

Packaging Quantity	100
Packaging Method	Tray

Other

Dielectric Material	LCP
---------------------	-----

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Pb (4% in Component Part)



Article Safe Usage Statements:
Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE’s information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) ‘Guidance on requirements for substances in articles’(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of ‘complex object’, the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA “Guidance on requirements for substances in articles” (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts

TE Part # ADP-SMPF-SMPF-G
SMP Jack to SMP Jack

TE Part # CONSMP005-G
SMP Jack 50 Ohm Cable

Customers Also Bought

TE Part #3-1879135-0
RN 0603 210K 0.1% 10PPM 1K RL

TE Part #2-1625886-0
1W SM M/OX 5% 47R

TE Part #4-1879496-7
CRGH0805 5% 1M0 0.33W

TE Part #2485264-1
DIP IC SOCKET 8P, GOLD FLASH



TE Part #2-2176371-1
[RQ 0603 7K5 0.1% 10PPM 5K RL](#)

TE Part #5227755-2
[BNC SOLDER RECEPT JACK SHORT](#)

TE Part #826629-7
[7P AMPMODU II HEADER](#)

TE Part #3-1879133-8
[RN 0603 2K1 0.1% 10PPM 1K RL](#)

TE Part #1-338069-0
[MICRO-MATCH SMD FTE](#)

TE Part #4-1825136-0
[A101SHZQ04](#)

Documents

Product Drawings

[SMP M Limited Detent SMD 18 GHz 50 Ohm](#)

English

CAD Files

Customer View Model

[ENG_CVM_CVM_2484640-1_1.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2484640-1_1.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2484640-1_1.3d_stp.zip](#)

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[rf-connectors-product-extension-flyer-en](#)

English

[test-probe-connector-en-flyer](#)

English

Product Specifications

[Product Specification](#)

English

2484640-1

SMP Connector, Plug, 50 ohm, Push-On, 0 – 18 GHz, Cable-to-Board, 1 Position,
Printed Circuit Board, Board Mount, -40 – 125 °C [-40 – 257 °F]

