TE Internal #: 2484787-1

SMA Connector, Jack, 50 ohm, Threaded, 0 – 18 GHz, Cable-to-Board, 1 Position, Printed Circuit Board, Board Mount, -65 – 165 $^{\circ}$ C


[-85 – 329 °F], Brass

View on TE.com >




Connectors > RF Connectors > Coax Connectors











RF Interface: SMA

RF Connector Style: Jack

Impedance: 50Ω

RF Connector Coupling Mechanism: Threaded

Operating Frequency: 0 – 18 GHz

Features

Product Type Features

| RF Interface | SMA |
|-----------------------------------|-----------------------|
| RF Connector Style | Jack |
| Connector System | Cable-to-Board |
| Sealable | No |
| Connector & Contact Terminates To | Printed Circuit Board |

Configuration Features

| PCB Mount Orientation | Right Angle |
|----------------------------|-------------|
| Number of Positions | 1 |
| Number of Coaxial Contacts | 1 |

Electrical Characteristics

| Impedance | 50 Ω | |
|-----------|------|--|
| ' | | |

Body Features

| Body Underplating Material | Nickel |
|----------------------------|--------|
| Body Material | Brass |
| | |



| Body Material Finish | Plated |
|----------------------------------------------|--------------------------------|
| Body Plating Material | Gold over Nickel |
| Contact Features | |
| RF Connector Contact Configuration | Captivated Contacts |
| RF Connector Center Contact Plating Material | Gold over Nickel |
| RF Connector Center Contact Material | Beryllium Copper |
| Termination Features | |
| Termination Method to PCB | Through Hole - Solder |
| Mechanical Attachment | |
| Panel Attachment Style | Rear Mount |
| RF Connector Coupling Mechanism | Threaded |
| Connector Mounting Type | Board Mount |
| RF Contact Captivation Method | Mechanical |
| Usage Conditions | |
| Operating Temperature Range | -65 – 165 °C[-85 – 329 °F] |
| Operation/Application | |
| Circuit Application | Signal |
| Operating Frequency | 0 – 18 GHz |
| Packaging Features | |
| Packaging Quantity | 100 |
| Packaging Method | Tray |
| Other | |
| Lockwasher Material | Brass |
| Dielectric Material | Polytetrafluoroethylene (PTFE) |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|-----------------------------------------------|---------------------------------------------|
| EU ELV Directive 2000/53/EC | Not Yet Reviewed |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2025 (247) |



Candidate List Declared Against: JAN 2025 (247)

SVHC > Threshold:

Pb (3.34% in Component Part)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



TE Part # 2466282-1 SMA PLUG STR SOLDER .085 .086 18 GHZ SUS













Documents



Product Drawings

SMA Jack RA PCB Thru Hole BHD 18 GHz

English

CAD Files

Customer View Model

ENG_CVM_CVM_2484787-1_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2484787-1_1.3d_stp.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2484787-1_1.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

rf-connectors-product-extension-flyer-en

English

test-probe-connector-en-flyer

English

Product Specifications

Product Specification

English