



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**
Connector & Housing Type: **Receptacle**
Number of Positions: **4**
Terminal Orientation: **Straight**
Primary Product Color: **Natural**

Features

Product Type Features

Connector & Contact Terminates To	Wire & Cable
Sealable	No
Connector & Housing Type	Receptacle

Configuration Features

Number of Positions	4
---------------------	---

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	With

Mechanical Attachment

Mating Alignment	With
------------------	------



Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	Polyamide
Dimensions	
Product Length	34.5 mm[1.36 in]
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Packaging Features	
Packaging Quantity	450
Packaging Method	Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 520947-1
FF 250/375 REC HSG 4P SECONDARY LOCK

TE Part # 281091-2
FF 375 REC 6-10MM2 TPBR

TE Part # 925475-1
FF 110 REC HSG 3P NYLON NAT

Also in the Series | FASTIN-FASTON 375

Crimp Terminal Housings(7)

Insertion & Extraction Tools(1)

Quick Disconnects(16)

Customers Also Bought

TE Part #3-1474654-6
FSN-21A-2

TE Part #172498-1
MIC PLUG HSG 13P (MK II)

TE Part #174200-1
250 FASTON HSG.,REC.,3 POS, NATRUAL

TE Part #964739-1
FLA-STE-GEH2,8 24P

TE Part #936863-1
FAMILY SEAL FOR HYB 42P CAP

TE Part #174204-1
250 FASTON HSG.,REC.,6 POS, NATRUAL

TE Part #174199-1
250 FASTON HSG.,REC.,3 POS, NATRUAL

TE Part #174202-1
250 FASTON HSG.,REC.,4 POS, NATRUAL

TE Part #1544317-2
PC 2V 8MM WP NG1 B

TE Part #85136-1
250 8P PLUG HSG (MK-II)



Documents

Product Drawings

FF 375 REC HSG 4P NYLON NAT

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_280073_H_c-280073-h.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_280073_H_c-280073-h.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_280073_H_c-280073-h.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

White Paper: Nylon Discoloration

English

Product Specifications

Application Specification

English