

FASTON | FASTON 375

TE Internal #: 280311-5


Receptacle, Receptacle, 1 Position, Straight, UL 94V-2, Black, Polyamide, Cable Mount (Free-Hanging), Carton, FASTON 375,

Crimp Terminal Housings

View on TE.com >



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: Receptacle

Connector & Housing Type: Receptacle

Number of Positions: 1

Terminal Orientation: Straight
UL Flammability Rating: UL 94V-2

Features

Product Type Features

Sealable	No
Connector & Housing Type	Receptacle
Configuration Features	
Number of Positions	1
Body Features	
Primary Product Color	Black
Contact Features	
Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	Without
Mechanical Attachment	
Mating Alignment	With

Cable Mount (Free-Hanging)

Connector Mounting Type



Housing Features

Housing Material	Polyamide
Dimensions	
Product Length	32.5 mm[1.279 in]
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Industry Standards	
UL Flammability Rating	UL 94V-2
Packaging Features	
Packaging Quantity	6000
Packaging Method	Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts






















Also in the Series | FASTON 375







Customers Also Bought





TE Part #735075-5 250 FASTON HSG. REC. 1P BLACK



TE Part #967558-1 J-P-T GEH 24P,ASSY



TE Part #150530-1 FASTON 375 AM REC 2-6MM2 0.2X1. 062 BR




TE Part #826947-5 5P MOD2 STIFT LEI



TE Part #280223-2 FASTON 375 ASY REC 4-6MM2 0.5X27. 0 TPBR




TE Part #8-1879337-9 CPF 0603 20K5 1% 50PPM 1K RL



TE Part #1326032-4 2.8MM RECP,SEAL,16AWG



TE Part #1587042-1 34P MALE CAP ASSY-KEY A



TE Part #6-1437667-1 4DB-P208-04=4DB ASSEMBLY



HD-20 VERRIEGLUNG

Documents

Product Drawings

FASTON 375 IS NYLON BLK

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_280311-5_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_280311-5_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_280311-5_L.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.