



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**
Connector & Housing Type: **Receptacle**
Number of Positions: **1**
Terminal Orientation: **Straight**
UL Flammability Rating: **UL 94V-2**

Features

Product Type Features

Sealable	No
Connector & Housing Type	Receptacle

Configuration Features

Number of Positions	1
---------------------	---

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	Without

Mechanical Attachment

Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)



Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Length	32.5 mm[1.279 in][1.35 in]
Wire Size	18 – 14 AWG

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94V-2
------------------------	----------

Packaging Features

Packaging Quantity	6000
Packaging Method	Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

TE Part # 280311-5
FASTON 375 IS NYLON BLK

Also in the Series | FASTON 375

Crimp Terminal Housings(2)

PCB Terminals(1)

Quick Disconnects(10)

Customers Also Bought

TE Part #2366517-3
FIX RING,CONN KIT

TE Part #280223-2
FASTON 375 ASY REC 4-6MM2 0.5X27.0 TPBR

TE Part #1438454-1
0.64MM,3 POSN SEALED PLUG ASSY

TE Part #2098253-1
SOC, SF, SIZE 16, 14-16 AWG, AU/SN

TE Part #HDP26-24-19SE
PLG, 19P, BLK, E, 12/16, S


TE Part #1-1379208-1
26W ASSY RECEPTACLE HSG

TE Part #2-1418483-1
2POS,AMP MCP2.8,REC. HSG

TE Part #142186-1
MIC TAB WITH LANCE



TE Part #1801178-6
3W RECEPTACLE HP CONNECTOR
BROWN



TE Part #2341467-1
REC CONN CVR,39POS,AMP MCP 2.8,
LOW BRKT

Documents

Product Drawings

IS 375 FASTON NYLON

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_280311_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_280311_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_280311_L.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.