2820350-4 - ACTIVE

TE Internal #: 2820350-4 INTERNAL Mini-SAS HD Cable Assembly, 16 Positions, 1 m [3.281 ft], 12 Gb/s, Black Cable, 30 AWG, .051 mm² Wire, INTERNAL Mini-SAS HD Plug End A

View on TE.com >



Cable Assemblies > Copper Cable Assemblies > Pluggable I/O Cable Assemblies



Cable Assembly Type: INTERNAL Mini-SAS HD

Number of Positions: 16

Cable Assembly Length: 1 m [3.281 ft]

Data Rate: 12 Gb/s

Cable Color: Black

Features

Product Type Features

Cable Assembly Category	High Speed, Industry Standard
Cable Assembly Type	INTERNAL Mini-SAS HD
Cable Style	Discrete Pairs
Cable Assembly (End A)	INTERNAL Mini-SAS HD Plug
Cable Assembly (End B)	INTERNAL Mini-SAS HD Plug
Configuration Features	
Number of Positions	16
Number of Pairs	8
Number of Signal Positions	16
Electrical Characteristics	
Impedance	100 Ω
Signal Characteristics	
Data Rate	12 Gb/s
Body Features	

2820350-4

INTERNAL Mini-SAS HD Cable Assembly, 16 Positions, 1 m [3.281 ft], 12 Gb/s, Black Cable, 30 AWG, .051 mm² Wire, INTERNAL Mini-SAS HD Plug End A



Cable Color	Black
Cable Flammability Rating	VW-1
Dimensions	
Wire Size	.051 mm ²
Outside Cable Diameter	1.02 mm, 1.68 mm[.04 in][.066 in]
Operation/Application	
Halogen Free	Yes
Other	
Cable Assembly Configuration	Double Ended
Cable Assembly Length	1 m[3.281 ft]
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247)

Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC

Not Low Halogen - contains Br or Cl > 900 ppm.

Solder Process Capability

Halogen Content

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

2820350-4

INTERNAL Mini-SAS HD Cable Assembly, 16 Positions, 1 m [3.281 ft], 12 Gb/s, Black Cable, 30 AWG, .051 mm² Wire, INTERNAL Mini-SAS HD Plug End A



Compatible Parts



TE Part # 2227640-1 1X2 VERT ASSY, MINI SAS HD INTERNAL

Customers Also Bought



•				
TE Part #1SNK706410R0000	TE Part #1SNK705912R0000	TE Part #1SNK712151R0000	TE Part #1SNK712011R0000	
ZK2.5-SF	EK2.5-4P	ZK16-PE-3P	ZK16-3P	



Documents

Product Drawings C/A, INTERNAL HD MINI SAS, 100 OHM, STR English

CAD Files

3D PDF

3D

2820350-4

INTERNAL Mini-SAS HD Cable Assembly, 16 Positions, 1 m [3.281 ft], 12 Gb/s, Black Cable, 30 AWG, .051 mm² Wire, INTERNAL Mini-SAS HD Plug End A



Customer View Model

ENG_CVM_CVM_2820350-4_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2820350-4_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2820350-4_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Product Specification

English