



TE Internal #: 282956-1

2 Position Housing, Housing for Female Terminals, Wire-to-Board / Wire-to-Device / Wire-to-Wire, 5 mm [.196 in] Centerline, Sealable, Black

[View on TE.com >](#)

Connectors > Automotive Connectors > Automotive Housings



Number of Positions: 2

Connector & Housing Type: **Housing for Female Terminals**

Mating Tab Width: **2.8 mm [.11 in]**

Connector System: **Wire-to-Board, Wire-to-Device, Wire-to-Wire**

Centerline (Pitch): **5 mm [.196 in]**

Features

Product Type Features

Connector Shape	Rectangular
Mixed & Hybrid Connector	No
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Board, Wire-to-Device, Wire-to-Wire
Sealable	Yes
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	2
Number of Rows	1

Electrical Characteristics

Nominal Voltage Architecture	12 V, 24 V
------------------------------	------------

Body Features

Primary Product Color	Black
-----------------------	-------



Connector & Keying Code	Neutral
Contact Features	
Contact Size	2.8mm
Contact Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Contact Current Rating (Max)	20 A
Mechanical Attachment	
Mating Alignment Type	Polarizing Slot
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	5 mm[.196 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F]
Operating Temperature Range	-30 – 125 °C[-22 – 257 °F]
Operation/Application	
Circuit Application	Power
Other	
Connector Position Assurance Capable	No
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 282955-1

SPLASH-PROOF FEM.CONN.HSG

Customers Also Bought

TE Part #1488991-4

3POS, MCON 1.2 CB REC 2p TL SEALED

TE Part #CAT-H396-M8649

Lockwashers and Panel Nuts for Deutsch HDP20

TE Part #2203973-1

26P SEALED PLUG, ASSY, KEY A

TE Part #184340-1

PLUG ASSY,2X2,CPA,W/O SLOT,CKT4 BLKD

TE Part #184346-1

2X2 CAP ASY KEY A C3

TE Part #1394277-2

SCHUTZKAP F4+7P GEH

TE Part #1-1438153-3

1X6 SEALED ASSY W/ CPA 6 CLSD

TE Part #CH02966001

QSZH-125-NR2-50MM



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_282956-1_D_c-282956-1-d.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_282956-1_D_c-282956-1-d.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_282956-1_D_c-282956-1-d.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Product Specification

English

2 POS. SPLASH PROOF CONNECTORS FOR 2.8mm SENSOR-FLAT CONTACTS

English