

Buchanan

TE Internal #: 284094-6


6 Position PCB Terminal Block, Header, Wire-to-Board, 5.08 mm [.2 in] Centerline, 1 Row, 90° Wire Entry Angle, 30 – 16 AWG, .05 – 1.31

mm² Wire


View on TE.com >



Connectors > Terminal Blocks & Strips > PCB Terminal Blocks











Number of Positions: 6

Terminal Block Connector Type: Header

Connector System: Wire-to-Board
Centerline (Pitch): 5.08 mm [.2 in]

Number of Rows: 1

Features

Product Type Features

Wire Protection	With
Terminal Block Connector Type	Header
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Stacking Configuration	Side Stackable
Stacked Levels	Without
Number of Positions	6
Number of Rows	1
Wire Entry Angle	90°
Wire Entry Location	Тор
Electrical Characteristics	
Operating Voltage	300 VAC



Primary Product Color	Green
Product Orientation	Right Angle
Contact Features	
Contact Mating Area Plating Material	Tin (Sn)
Contact Base Material	Brass
Contact Current Rating (Max)	13.5 A
Termination Features	
Termination Post & Tail Length	3.5 mm[.138 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Screw Plating Material	Nickel
Screw Material	Brass
Thread Size	M3
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	PA 66
	PA 66 5.08 mm[.2 in]
Housing Material	
Housing Material Centerline (Pitch)	
Housing Material Centerline (Pitch) Dimensions	5.08 mm[.2 in]
Housing Material Centerline (Pitch) Dimensions Wire Size	5.08 mm[.2 in]
Housing Material Centerline (Pitch) Dimensions Wire Size Usage Conditions	5.08 mm[.2 in] 30 – 16 AWG
Housing Material Centerline (Pitch) Dimensions Wire Size Usage Conditions Operating Temperature Range	5.08 mm[.2 in] 30 – 16 AWG
Housing Material Centerline (Pitch) Dimensions Wire Size Usage Conditions Operating Temperature Range Operation/Application	5.08 mm[.2 in] 30 – 16 AWG -40 – 110 °C[-40 – 230 °F]
Housing Material Centerline (Pitch) Dimensions Wire Size Usage Conditions Operating Temperature Range Operation/Application Circuit Application	5.08 mm[.2 in] 30 – 16 AWG -40 – 110 °C[-40 – 230 °F]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions



China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (.74% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought













TE Part #2102735-1 BP, Half Left End, MULTIGIG RT 2R




TE Part #2102737-1 BP, Right End, MULTIGIG RT 2R



TE Part #1888251-2 Low Profile,RJ45,1x4,Bi-Color





TE Part #284093-6 TERMI-BLOK PCB MOUNT 90, 5,0MM



Documents

Product Drawings

TERMI-BLOK PCB MOUNT 90, 5,08M

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_284094-6_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_284094-6_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_284094-6_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

BUCHANAN TERMINAL BLOCKS CATALOG - EUROSTYLE TERMINAL BLOCKS

English

1-1773458-1_EURO_STYLE_TERMINAL_BLOCKS_QRG

English

Product Specifications

Application Specification

English

6 Position PCB Terminal Block, Header, Wire-to-Board, 5.08 mm [.2 in] Centerline, 1 Row, 90° Wire Entry Angle, 30 – 16 AWG, .05 – 1.31 mm² Wire



Agency Approvals

UL

English