#### **AMP CT**

TE Internal #: 292133-7


PCB Mount Header, Vertical, Wire-to-Board, 7 Position, 2 mm [.078 in] Centerline, Partially Shrouded, Tin (Sn), Through Hole - Solder,

AMP CT

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > CT 2mm Post Header Assembly: Box-V











PCB Connector Type: PCB Mount Header

PCB Mount Orientation: Vertical
Connector System: Wire-to-Board

Number of Positions: 7
Number of Rows: 1

All CT 2mm Post Header Assembly: Box-V (15)

### **Features**

### **Product Type Features**

PCB Connector Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

### **Configuration Features**

PCB Mount Orientation	Vertical
Number of Positions	7
Number of Rows	1

#### **Electrical Characteristics**

Operating Voltage	125 VDC
	120 12 0



### **Body Features**

Primary Product Color	Natural
Contact Features	
Mating Pin Diameter	.6 mm[.024 in]
PCB Contact Termination Area Plating Material Thickness	1 μm[39.37 μin]
Contact Shape & Form	Round
Contact Layout	Inline
Contact Mating Area Length	4.2 mm[.165 in]
Contact Base Material	Brass
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Tin (Sn)
Contact Type	Pin
Contact Current Rating (Max)	4 A
Termination Features	
Termination Post & Tail Diameter	.6 mm[.024 in]
Termination Post & Tail Length	3.2 mm[.126 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Panel Mount Feature	Without
Mating Retention Type	Polarized Lock
Mating Retention	Without
Mating Alignment Type	Polarization
PCB Mount Retention	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount
Mating Alignment	With
Housing Features	
Housing Material	Nylon 66
Centerline (Pitch)	2 mm[.078 in]
Dimensions	
Connector Width	5.8 mm[.228 in]
PCB Thickness (Recommended)	.8 mm[.031 – .063 in]



Connector Height	6.8 mm[.267 in]
Connector Length	15.8 mm[.622 in]
Usage Conditions	
Operating Temperature Range	-30 - 105 °C[-22 - 221 °F]
Operation/Application	
Assembly Process Feature	Pick and Place Cover
Circuit Application	Power & Signal
Circuit Application  Industry Standards	Power & Signal
	Power & Signal  UL 94V-0
Industry Standards	
Industry Standards  UL Flammability Rating	

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach




## Compatible Parts



HOUSINGS




## Also in the Series | AMP CT







Connector Hardware(46)



PCB Headers & Receptacles(756)



Rectangular Connector Housings (90)




Rectangular Power Connectors(924)



Standard Rectangular Connectors(176)



Wire-to-Board Connector Assemblies & Housings(79)



Wire-to-Board Headers & Receptacles (756)


# Customers Also Bought



TE Part #292207-4 MINI CT SGL DIP V 4P NAT



TE Part #2-292206-5 MINI CT SGL DIP H 5P BLACK



TE Part #2-292173-7 CT BOX HDR H SMT 7P O/TAPE BLA



TE Part #1-292227-0
1.5 MINI CT SGL H SMT W BOSS 1

PCB Mount Header, Vertical, Wire-to-Board, 7 Position, 2 mm [.078 in] Centerline, Partially Shrouded, Tin (Sn), Through Hole - Solder, AMP CT





TE Part #292228-8

1.5 MINI CT SGL H SMT W/O BOSS



TE Part #292207-9 MINI CT SGL DIP V 9P NAT



TE Part #CAT-3983178-PHBXVD
CT 2mm Post Header Asmbly: Box V
DIP



TE Part #292228-3 1.5 MINI CT SGL H SMT W/O BOSS

TE Part #9-292131-0 SGL HDR ASSY BOX DIP V POLARIS

### **Documents**

### **Product Drawings**

CT P/HDR ASSY BOX V 7P W/O KIN

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_292133-7\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_292133-7\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_292133-7\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### **Product Specifications**

Workmanship Specification

English