

TE Internal #: 292331-3

Board-to-Board, 3 Position, 1.6 mm [.063 in] Centerline, Receptacle, Right Angle, Printed Circuit Board, Signal, Board Mount, DC Jack

Connectors

View on TE.com >



Connectors > PCB Connectors > Battery Connectors & Holders > DC Jack Connectors



Connector System: Board-to-Board

Number of Positions: 3

Centerline (Pitch): 1.6 mm [.063 in]

Connector & Housing Type: Receptacle

PCB Mount Retention: Without

Features

Product Type Features

Connector System	Board-to-Board
Connector & Housing Type	Receptacle
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	3
PCB Mount Orientation	Right Angle

Contact Features

PCB Contact Termination Area Plating Material	Tin-Lead
Contact Underplating Material	Nickel
Contact Mating Area Plating Material	Gold (Au)
Contact Current Rating (Max)	2 A

Mechanical Attachment

PCB Mount Retention	Without
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	1.6 mm[.063 in]
--------------------	-----------------

Usage Conditions

Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
-----------------------------	---------------------------



Operation/Application

Circuit Application	Signal	
---------------------	--------	--

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought





TE Part #L9000220-01
Antenna WiFi6/6E FPC SH 12x12 50
MHF4



TE Part #1746142-1 LEAF TYPE BATTERY CONN 3P



TE Part #2-32562-1 PIDG SPDFLG 22-16COMM22-18MIL6



TE Part #3-965261-1 FLACHSTE-GEH2,8 4P



TE Part #1932869-1 FBIS-II REC ASSY 6 POS, 0.5um Gold



TE Part #1761608-9
IDC LOW PRO HDR 26P VERT SHT LAT BLK



TE Part #1445049-2 FREE HANG SNGL ROW HSG 2 POS



TE Part #292448-1
3.0mm PITCH 3P SMT ASSEMBLY
BATTERY CONN



TE Part #2336582-1
PUSH-PUSH NANO SIM CONNECTOR



TE Part #1981061-1 LEAF BATTERY CONN W/B 3POS. P=3.2, PKG

Documents

Product Drawings

BATTERY 3P SMT 1.6MM PITCH ASSEMBLY CONN

English

CAD Files

Customer View Model

ENG_CVM_292331-3_B2.3d_igs.zip

English

Customer View Model

ENG_CVM_292331-3_B2.3d_stp.zip

English

Customer View Model

ENG_CVM_292331-3_B2.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Board-to-Board, 3 Position, 1.6 mm [.063 in] Centerline, Receptacle, Right Angle, Printed Circuit Board, Signal, Board Mount, DC Jack Connectors



Products for Mobile Equipment

English

Product Specifications

Product Specification

English