



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: **General Purpose Power Relay**

Current Type: **DC**

Coil Magnetic System: **Monostable**

Contact Arrangement: **2 Form A DPST-NO**

Contact Current Rating: **8 A**

Features

Product Type Features

Relay & Contactor Type	General Purpose Power Relay
------------------------	-----------------------------

Configuration Features

Contact Number of Poles	2
Coil Special Features	UL Coil Insulation Class F
Contact Arrangement	2 Form A DPST-NO

Electrical Characteristics

Contact Limiting Making Current	15 A
Contact Limiting Continuous Current	8 A
Contact Limiting Breaking Current	8 A
Insulation Initial Dielectric Between Open Contacts	1000 Vrms
Insulation Initial Dielectric Between Adjacent Contacts	2500 Vrms
Contact Switching Voltage (Max)	400 VAC
Coil Resistance	1440 Ω
Contact Current Rating	8 A



Coil Voltage Rating	24 VDC
Contact Voltage Rating	250 VAC
Coil Power Rating DC	.4 W
Insulation Initial Dielectric Between Contacts & Coil	5000 Vrms

Body Features

Product Weight	13 g[.459 oz]
Enclosure Type	Flux Resistant Automatic Solder Capable & Washable

Contact Features

Contact Material	AgNi90/10
------------------	-----------

Termination Features

Main Termination & Connection Type	Solder Pins
Coil Termination & Connection Type	Solder Pins

Mechanical Attachment

Product Mount Type	Board Mount
--------------------	-------------

Dimensions

Insulation Clearance Between Contact & Coil	10 mm[.394 in]
Insulation Creepage Between Contact & Coil	10 mm[.394 in]
Product Width	12.7 mm[.5 in]
Product Length	29 mm[1.14 in]
Product Height	15.7 mm[.618 in]

Usage Conditions

Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
Environmental Category of Protection	RTIII
Environmental Ambient Temperature (Max)	85 °C[185 °F]

Operation/Application

Solder Process	Wave Solder Capable
Current Type	DC
Coil Magnetic System	Monostable

Packaging Features

Packaging Method	Carton, Tube
------------------	--------------

Other



Coil Power Rating Class	.3 – .4 W
Contact Current Class	5 – 10 A
Environmental Ambient Temperature Class	70 – 85 °C
Height Class (Mechanical)	15 – 16 mm
Length Class (Mechanical)	25 – 30 mm
Width Class (Mechanical)	12 – 16 mm

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 2022103-1
[RT17017](#)



TE Part # 8-1415036-1
[PTML1024](#)



TE Part # 1860991-1
[RT78602, RELAY SOCKET PCB 5MM](#)




TE Part # 5-1415036-1
[PTML0024](#)



TE Part # 9-1415036-1
[PTMT00A0](#)



TE Part # 6-1415035-1
[RT78726](#)



TE Part # 3-1415036-1
[PTMG0524](#)




TE Part # 1415540-8
[RT28816](#)



TE Part # 1860200-1
[RT7872P](#)



TE Part # 6-1415036-1
[PTML0524](#)



TE Part # 1860306-1
[RT78725](#)



TE Part # 1415037-1
[PTMT00L0](#)




TE Part # 2-1415036-1
[PTMG0024](#)

Also in the Series | [SCHRACK Power PCB Relay RT2](#)



[AC Relays\(17\)](#)






[General Purpose Power Relays\(106\)](#)



[PCB Relays\(106\)](#)

Customers Also Bought



 TE Part #173926-1 4 P ACTION PIN UMNL	 TE Part #1934225-1 Tin Man Recept Assy 4 Pair 16 Column	 TE Part #1-1123724-2 3.96EP HDR ASSY 2(3)P NATURAL	 TE Part #1658622-3 16 NOVO MIL/CTR 30DP, LEAD FREE
 TE Part #6-1437719-6 T01-0570-S03-FEMALE REC PANEL-PCB STRT	 TE Part #5-826947-0 MOD2 PIN HEADER 50P	 TE Part #165564-1 110 PIDG FASTON REC	 TE Part #5-147377-2 20 SYS50 SMT HDR DR SHD SN
 TE Part #1-1879663-5 H8 150R 0.1% 15PPM	 TE Part #7-1437719-2 T01-0570-S05-FEMALE REC PANEL-PCB STRT		

Documents

CAD Files

Customer View Model

ENG_CVM_CVM_3-1393243-3_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-1393243-3_C.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_3-1393243-3_C.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Power PCB Relay RT2

English

Product Specifications



Definitions General Purpose Relays

English

Agency Approvals

VDE Certificate

English