TE Internal #: 3-2273124-1

M8 to M12 Cable Assembly, 3 Position, .3 m, Sensor/Actuator, A

Code, M8 Plug End A, M12 Socket End B, Double Ended, Plastic

View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies > M8 Male Straight to Female LED Double Ended Cable



Cable Assembly Type: M8 to M12

Number of Positions: 3

Cable Assembly Length: .3 m

M8/M12 Application Type: Sensor/Actuator

Connector & Keying Code: A

All M8 Male Straight to Female LED Double Ended Cable (20)

#### **Features**

#### **Product Type Features**

Cable Assembly Type	M8 to M12
Cable Assembly (End A)	M8 Plug
Cable Assembly (End B)	M12 Socket

#### **Configuration Features**

Number of Positions	3	

#### **Electrical Characteristics**

Operating Voltage	24 VDC

#### **Body Features**

Jacket Material	PUR
Connector Color (End B)	Black
Connector Color (End A)	Black
Cable Color	Black
Wire Color (Base)	Brown, Blue, Black
Connector & Keying Code	A

#### **Contact Features**

Contact Current Rating (Max)	4 A	

#### Mechanical Attachment



Thread Size	M8 x M8
Connector Orientation (End A)	Right Angle
Connector Orientation (End B)	Straight
Housing Features	
Housing Material	Plastic
Dimensions	
Outside Cable Diameter	4.1 mm[.161 in]
Wire Size	22 AWG
Usage Conditions	
Operating Temperature Range	-40 – 90 °C[-40 – 194 °F]
Operation/Application	
Indicator Type	LED
M8/M12 Application Type	Sensor/Actuator
Shielded	No
Packaging Features	
Packaging Method	D .
r dekaging wethod	Box
Packaging Quantity	25
Packaging Quantity	
Packaging Quantity  Other	25

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**



# **Customers Also Bought**



#### **Documents**

**Product Drawings** 

M8 angled scket to M8 strght plug 2 LED

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_3-2273124-1\_A.2d\_dxf.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_3-2273124-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_3-2273124-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

**Product Specifications** 

**Product Specification** 

English