



MTA 100

TE Internal #: 3-640440-2

Connector Assembly, Receptacle, Insulation Displacement (IDC),  
Wire-to-Board, Tin (Sn), MTA 100, Rectangular Wire & Cable  
Connectors & Housings

[View on TE.com >](#)

Connectors > Rectangular Connectors > Standard Rectangular Connectors > MTA Receptacle: Nylon, Tin Plated, 2.54 mm



Connector Product Type: **Connector Assembly**

Connector & Housing Type: **Receptacle**

Mating Alignment: **Without**

Mating Retention: **With**

Mating Retention Type: **Locking Ramp**

[All MTA Receptacle: Nylon, Tin Plated, 2.54 mm \(167\)](#)

Features

Product Type Features

|                                    |                    |
|------------------------------------|--------------------|
| Compatible With Discrete Wire Type | Stranded           |
| Connector Product Type             | Connector Assembly |
| Connector & Housing Type           | Receptacle         |
| Connector System                   | Wire-to-Board      |
| Insertion Force Type               | Normal             |
| Sealable                           | No                 |
| Connector & Contact Terminates To  | Wire & Cable       |

Configuration Features

|                     |     |
|---------------------|-----|
| Number of Cavities  | 2   |
| Contacts Preloaded  | Yes |
| Number of Positions | 2   |
| Number of Rows      | 1   |



Electrical Characteristics

|                   |         |
|-------------------|---------|
| Operating Voltage | 250 VAC |
|-------------------|---------|

Body Features

|                       |     |
|-----------------------|-----|
| Primary Product Color | Red |
|-----------------------|-----|

Contact Features

|                                                |            |
|------------------------------------------------|------------|
| Contact Underplating Material                  | Nickel     |
| Wire Contact Termination Area Plating Material | Tin        |
| Contact Type                                   | Receptacle |
| Contact Mating Area Plating Material           | Tin (Sn)   |
| Contact Retention Within Housing               | With       |
| Contact Current Rating (Max)                   | 5 A        |

Termination Features

|                                    |                               |
|------------------------------------|-------------------------------|
| Termination Method to Wire & Cable | Insulation Displacement (IDC) |
|------------------------------------|-------------------------------|

Mechanical Attachment

|                                       |                            |
|---------------------------------------|----------------------------|
| Contact Retention Type Within Housing | Locking Lance              |
| Mating Alignment                      | Without                    |
| Mating Retention                      | With                       |
| Mating Retention Type                 | Locking Ramp               |
| Connector Mounting Type               | Cable Mount (Free-Hanging) |

Housing Features

|                    |                |
|--------------------|----------------|
| Housing Material   | Nylon          |
| Centerline (Pitch) | 2.54 mm[.1 in] |

Dimensions

|                  |                  |
|------------------|------------------|
| Connector Width  | 6.99 mm[.275 in] |
| Connector Height | 13.21 mm[.52 in] |
| Wire Size        | 22 AWG           |
| Connector Length | 5.08 mm[.2 in]   |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | -55 – 105 °C[-67 – 221 °F] |
|-----------------------------|----------------------------|

Operation/Application

|                     |        |
|---------------------|--------|
| Shielded            | No     |
| Circuit Application | Signal |



Industry Standards

|                                             |            |
|---------------------------------------------|------------|
| Compatible With Agency/Standards Products   | CSA, UL    |
| UL Rating                                   | Recognized |
| Compatible With Approved Standards Products | UL E28476  |
| CSA Rating                                  | LR 7189    |
| UL Flammability Rating                      | UL 94V-2   |

Packaging Features

|                    |         |
|--------------------|---------|
| Packaging Quantity | 500     |
| Packaging Method   | Package |

Product Compliance

For compliance documentation, visit the product page on TE.com>






|                                               |                                                                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                     |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                     |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                       |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2025 (247)<br>Candidate List Declared Against: JAN 2025 (247)<br>Does not contain REACH SVHC |
| Halogen Content                               | BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.                                                                        |
| Solder Process Capability                     | Not applicable for solder process capability                                                                                  |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




|                                                                                                                                                                                          |                                                                                                                                                                                       |                                                                                                                                                                                      |                                                                                                                                                                                        |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  <p>TE Part # CAT-104MTA-PVUNH<br/>PCB Header: Polyester, Vertical, Unshrouded, No Mating Alignment</p> |  <p>TE Part # CAT-104MTA-NVTHH<br/>Nylong Vertical PCB Header: 2.54mm, Through Hole, MTA 100</p>    |  <p>TE Part # 58246-3<br/>MTA 100 CRIMP HEAD PRODUCTION RBBN CABLE</p>                            |  <p>TE Part # 58579-1<br/>MTA 100 MANUAL TOOL ASSEMBLY DISCRETE</p>                                 |
|  <p>TE Part # 2-2232980-2<br/>02P MTA100 HDR ASSY, FL, SM, SN</p>                                      |  <p>TE Part # 3-647051-2<br/>02P MTA100 HRD ASSYF/L HT LF</p>                                      |  <p>TE Part # CAT-104MTA-PVSHH<br/>Polyester Vertical PCB Header: 2.54 mm, Shrouded, MTA 100</p> |  <p>TE Part # CAT-104MTA-NTPMP<br/>MTA Plug: Nylon, Tin Plated, 2.54 mm, with Mating Alignment</p> |
|  <p>TE Part # 3-647106-2<br/>02P MTA-100 HDR ASSY,SM,SN</p>                                           |  <p>TE Part # 58246-1<br/>MTA 100 CRIMP HEAD REPAIR DISCRETE</p>                                  |  <p>TE Part # 640454-2<br/>02P MTA100 HDR ASSY SQ STR POL</p>                                   |  <p>TE Part # CAT-104MTA-PRSMH<br/>PCB Header, Right Angle, Polyester, 2.54 mm</p>                |
|  <p>TE Part # CAT-104MTA-PRUSH<br/>PCB Header: Polyester, Right Angle, Unshrouded</p>                 |  <p>TE Part # CAT-104MTA-PVBRH<br/>Polyester Vertical PCB Header: 2.54 mm, Breakaway, MTA 100</p> |  <p>TE Part # 640550-2<br/>02P MTA100 COVER</p>                                                 |  <p>TE Part # 58246-2<br/>MTA 100 CRIMP HEAD PRODUCTION DISCRETE</p>                              |
|  <p>TE Part # 58074-1<br/>MTA 50/100/156 MANUAL TOOL FRAME</p>                                        |  <p>TE Part # CAT-104MTA-NYLCC<br/>Nylon PCB Connector Covers: 2.54 mm, MTA 100</p>               |  <p>TE Part # 3-644694-2<br/>02P MTA100 R/A HDR RETENTIVE</p>                                   |  <p>TE Part # CAT-104MTA-PRUMH<br/>PCB Header: Polyester, Right Angle, 2.54 mm</p>                |

Also in the Series | [MTA 100](#)



Connector Caps & Covers(69)




Connector Contacts(8)



Connector Hardware(1)




PCB Headers & Receptacles(441)



Rectangular Connector Housings(1)



Rectangular Power Connectors(1)



Standard Rectangular Connectors(496)



Wire-to-Board Headers & Receptacles (441)

Customers Also Bought



TE Part #2176464-8  
HCH215 300W 100R 5% LEAD




TE Part #3-640431-3  
03P MTA156 CONN ASSY 18AWG ORA



TE Part #3-640432-4  
04P MTA156 CONN ASSY 20AWG YEL



TE Part #CAT-104MTA-NTPNR  
MTA Receptacle: Nylon, Tin Plated, 2.54 mm



TE Part #640550-2  
02P MTA100 COVER



TE Part #1-2176312-8  
RP 1E 0.1W 18K7 0.1% 25PPM 1K RL



TE Part #3-647000-2  
02P MTA100 PSTD CONN ASSY LF

Documents

Product Drawings

02P MTA100 CONN ASSY 22AWG RED

English

CAD Files

Customer View Model

ENG\_CVM\_CVM\_3-640440-2\_L.2d\_dxf.zip

English

3D PDF



3D

Customer View Model

[ENG\\_CVM\\_CVM\\_3-640440-2\\_L.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_3-640440-2\\_L.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

Agency Approvals

[UL](#)

English

[UL](#)

English