




MTA 156

TE Internal #: 3-644468-4
Connector Assembly, Receptacle, Insulation Displacement (IDC),
Wire-to-Board, Tin (Sn), MTA 156, Rectangular Wire & Cable
Connectors & Housings

[View on TE.com >](#)

Connectors > Rectangular Connectors > Standard Rectangular Connectors



Connector Product Type: **Connector Assembly**
Connector & Housing Type: **Receptacle**
Mating Alignment: **With**
Mating Alignment Type: **Polarization**
Mating Retention: **With**

Features

Product Type Features

Compatible With Discrete Wire Type	Stranded
Connector Product Type	Connector Assembly
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Cavities	4
Contacts Preloaded	Yes
Number of Positions	4
Number of Rows	1

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Body Features



Primary Product Color	White
-----------------------	-------

Contact Features

Contact Underplating Material	Nickel
Wire Contact Termination Area Plating Material	Tin
Contact Type	Receptacle
Contact Mating Area Plating Material	Tin (Sn)
Contact Retention Within Housing	With
Contact Current Rating (Max)	7 A

Termination Features

Termination Method to Wire & Cable	Insulation Displacement (IDC)
------------------------------------	-------------------------------

Mechanical Attachment

Contact Retention Type Within Housing	Locking Lance
Mating Alignment	With
Mating Alignment Type	Polarization
Mating Retention	With
Mating Retention Type	Locking Ramp
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	Nylon
Centerline (Pitch)	3.96 mm[.156 in]

Dimensions

Connector Width	9.78 mm[.385 in]
Connector Height	18.42 mm[.725 in]
Wire Size	24 AWG
Connector Length	15.85 mm[.624 in]

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Shielded	No
Circuit Application	Power

Industry Standards

--	--



Compatible With Agency/Standards Products	CSA, UL
UL Rating	Recognized
Compatible With Approved Standards Products	UL E28476
CSA Rating	LR 7189
UL Flammability Rating	UL 94V-2

Packaging Features

Packaging Quantity	250
Packaging Method	Bag/Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



TE Part # 2-647125-4
04P MTA156 SHRD HDR ASSY LF



TE Part # 3-644611-4
04P MTA156 HDR POL WO PEGS LF



TE Part # 3-644615-4
04P MTA156 POL HDR ASSY LF



TE Part # 3-644617-4
04P MTA156 HDR ASY PO RA FB LF



TE Part # 644752-4
04P MTA156 HDR ASSY SQ STR F/L




TE Part # 643493-1
04P MTA156 HDR ASSY STR W/O#2



TE Part # 640551-4
04P MTA156 COVER



TE Part # 59804-1
MAINTENANCE TOOL



TE Part # 640643-4
04P MTA156 COVER F/T




TE Part # 643071-4
04P MTA156 FD-THRU COVER




TE Part # 58074-1
MTA 50/100/156 MANUAL TOOL FRAME



TE Part # 640385-4
04P MTA156 HDR ASSY SQ R/A




TE Part # 640388-4
04P MTA156 HDR ASSY RN STR F/L



TE Part # 640445-4
04P MTA156 HDR ASSY FL/STR SN



TE Part # 644751-4
04P MTA156 HDR ASSY R/A



TE Part # 644753-4
04P MTA156 HDR ASSY RN STR F/L



TE Part # 643067-4
04P MTA156 CMOLDED COVER



TE Part # 643493-3
04P MTA156 HDR ASSY W/O#2,3



TE Part # 644749-4
04P MTA156 HDR ASSY STR SQ SN




TE Part # 2-647127-4
04P MTA156 SHRD HDR ASSY LF

Also in the Series | **MTA 156**




Connector Caps & Covers(89)




Connector Contacts(4)



Connector Hardware(2)



PCB Headers & Receptacles(677)



Power Contacts(3)



Rectangular Power Connectors(1178)




Standard Rectangular Connectors(667)

Customers Also Bought



TE Part #643429-1
15P UMNL HDR ASSY POL




TE Part #3-644564-4
04P MTA100 CONN ASSY F/T 26AWG



TE Part #3-641524-4
04P MTA156 POST CON ASSY LF



TE Part #CAT-104MTA-NTPNR
MTA Receptacle: Nylon, Tin Plated, 2.54 mm



TE Part #3-640602-4
04P MTA156 CONN ASSY 24AWG LF




TE Part #3-641437-4
04P MTA156 PSTD CONN ASSY RED



TE Part #3-640602-3
03P MTA156 CONN ASSY 24AWG LF



TE Part #3-641438-4
04P MTA156 PSTD CONN ASSY WHT



TE Part #3-647016-4
04P MTA100 PSTD CONN ASSY LF

Documents



Product Drawings

04P MTA156 CONN ASSY 24AWG LF

English

CAD Files

Customer View Model

ENG_CVM_3-644468-4_D.3d_igs.zip

English

Customer View Model

ENG_CVM_3-644468-4_D.3d_stp.zip

English

Customer View Model

ENG_CVM_3-644468-4_D.2d_dxf.zip

English

3D PDF

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-644468-4_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-644468-4_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-644468-4_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

Japanese

Application Specification

English

MTA 156 Ribbon Cable Connector Assemblies (English And Spanish)

English

MTA 156 Ribbon Cable Connector Assemblies (English And Spanish)

Japanese

Application Specification

English

Agency Approvals

Agency Approval Document

English

