

### **AMP-IN**

TE Internal #: 3-770565-1

PCB Pin, 1.83 mm [.072 in] PCB Hole, 22 – 18 AWG, .3 – .9 mm<sup>2</sup> Wire, Through Hole - Solder, Tin Plating, Reel, PCB Terminals

View on TE.com >



Terminals & Splices > PCB Terminals











PCB Terminal Type: PCB Pin

PCB Thickness (Recommended): 1.57 mm [ .062 in ]

PCB Hole Diameter: 1.83 mm [ .072 in ] Profile Height from PCB: 1.73 mm [.068 in]

Compatible Insulation Diameter (Max): 2.79 mm [ .11 in ]

### **Features**

## Product Type Features

Terminal Features	Stud Hole
Contact Features	
Terminal Plating Finish	Bright
Contact Mating Area Plating Material Thickness	4 μm[157.48 μin]
PCB Terminal Type	PCB Pin
Terminal Plating Material	Tin
Contact Underplating Material	Brass
Terminal Size	Miniature
Terminal Orientation	Straight
Termination Features	
Termination Method to PCB	Through Hole - Solder
Product Terminates To	Printed Circuit Board
Mechanical Attachment	
Wire Insulation Support	With



#### **Dimensions**

Extension Below Board	2.29 mm[.09 in]
PCB Thickness (Recommended)	1.57 mm[.062 in]
PCB Hole Diameter	1.83 mm[.072 in]
Profile Height from PCB	1.73 mm[.068 in]
Compatible Insulation Diameter (Max)	2.79 mm[.11 in]
Compatible Insulation Diameter Range	1.52 – 2.79 mm[.06 – .11 in]
Wire Size	$.39 \text{ mm}^2$

### **Usage Conditions**

Insulation Option	Uninsulated
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Packaging Features	
Packaging Quantity	7000

Reel

## **Product Compliance**

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts






OCEAN\_2.0\_Applicator-S-062F110F-













# Customers Also Bought























### **Documents**

### **Product Drawings**

MINI AMP-IN 22-18 AWG SN/BRASS LF

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_3-770565-1\_G.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_3-770565-1\_G.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_3-770565-1\_G.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## **Product Specifications**

**Application Specification** 

English