

#### **SOLISTRAND**

TE Internal #: 320344

Closed Ring Tongue Terminal, 6 AWG, 1/2 / M12 Stud, 13.08 mm [.

515 in] Stud Diameter, Closed Barrel, Straight, Tin Plating,

Uninsulated

View on TE.com >



Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 20800 - 33100 CMA

Stud Size: 1/2, M12

## **Features**

## **Product Type Features**

Troduct Type reductes	
Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	1/2, M12
Sealable	No
Wire Insulation Support Retention Type	Non-Insulation Support
Configuration Features	
Number of Holes	1
Body Features	
Product Weight	6.017 g
Contact Features	
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Tin
Mechanical Attachment	
Wire Insulation Support	Without



Wire Size	20800 – 33100 CMA
Stud Diameter	13.08 mm[.515 in]
Tongue Thickness	.79 mm[.031 in]
Product Length	46.74 mm[1.837 in]
Barrel Inside Diameter	5.89 mm[.231 in]
Usage Conditions	

#### **Usage Conditions**

Insulation Option	Uninsulated	

## Operation/Application

Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin

## **Industry Standards**

## **Packaging Features**

Packaging Quantity	100
Packaging Method	Loose Piece

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



TE Part # 69217
HYP8/10 SOLIS 6AWG DIE SET












# **Customers Also Bought**





















TE Part #2-304668-9 SPRING

## **Documents**

## **Product Drawings**

TERMINAL, SOLIS R 6 1/2

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_320344\_L.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_320344\_L.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_320344\_L.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_320344\_G.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_320344\_G.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_320344\_G.2d\_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### **Instruction Sheets**

Instruction Sheet (U.S.)

English

## **Agency Approvals**

UL

English

Closed Ring Tongue Terminal, 6 AWG, 1/2 / M12 Stud, 13.08 mm [.515 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Uninsulated

