

SOLISTRAND

TE Internal #: 322246

Butt Splice, 2 AWG, 34 – 35 mm² Wire, Sight Hole, 52600 – 83700

CMA, Copper, 32.13 mm [1.265 in] Length, Loose Piece, Closed

Barrel

View on TE.com >



Terminals & Splices > Splices











Splice Type: Butt Splice
Wire Size: 34 – 35 mm²

Sealable: No

Splice Features: Sight Hole

Features

Product Type Features

Splice Accessory Type	Splice
Splice Type	Butt Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

	Compatible With Wire & Cable Type Discrete Wire	
--	---	--

Body Features

Product Weight	20.249 g
Splice Features	Sight Hole

Contact Features

Terminal Plating Material	Tin
Contact Base Material	Copper
Barrel Type	Closed



Mechanical Attachment

Wire Insulation Support	Without
Dimensions	
Outside Diameter	13.7 mm[.539 in]
Wire Size	52600 – 83700 CMA
Barrel Inside Diameter	9.39 mm[.37 in]
Terminal Material Thickness	1.85 mm[.073 in]
Product Length	32.13 mm[1.265 in]
Usage Conditions	
Insulation Option	Uninsulated
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	50
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts






















Customers Also Bought





TE Part #2-1616921-3
K400B1F=CONTACTOR-SPST NO



TE Part #YWM11BW03-03PN0000
RECEPT ASSY.WM. IN-LINE.SIZE 3 3
WAY



TE Part #4-1437567-5 MPE206R=(MSPE) SW P/B WATERPRO















Documents

Product Drawings
SPLICE, SOLIS BUTT 2

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_322246_J.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_322246_J.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_322246_J.3d_stp.zip

English

Customer View Model

ENG_CVM_322246_B.3d_igs.zip

English

Butt Splice, 2 AWG, 34 – 35 mm² Wire, Sight Hole, 52600 – 83700 CMA, Copper, 32.13 mm [1.265 in] Length, Loose Piece, Closed Barrel



Customer View Model

ENG_CVM_322246_B.3d_stp.zip

English

Customer View Model

ENG_CVM_322246_B.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL

English