



Terminals & Splices > Splices



Splice Type: **Parallel Splice**

Wire Size: **.3 – 1.42 mm²**

Sealable: **No**

Splice Features: **Serrated**

Features

Product Type Features

Splice Accessory Type	Splice
Style Code	B
Splice Type	Parallel Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Body Features

Product Weight	1.382 g
Splice Features	Serrated
Primary Product Color	Orange

Contact Features

Terminal Plating Material	Nickel
---------------------------	--------



Contact Base Material	Nickel
Barrel Type	Closed

Mechanical Attachment

Wire Insulation Support	Without
-------------------------	---------

Dimensions

Outside Diameter	3.58 mm[.141 in]
Wire Size	509 – 3260 CMA
Barrel Inside Diameter	1.55 mm[.061 in]
Terminal Material Thickness	.76 mm[.03 in]
Product Length	7.65 mm[.301 in]

Usage Conditions

Insulation Option	Uninsulated
-------------------	-------------

Operation/Application

Compatible With Wire Base Material	Copper
------------------------------------	--------

Industry Standards

Government Qualified Splice	No
-----------------------------	----

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



REPRESENTATION ONLY

TE Part # 46447  
DAHT STRATO 22-10 ASSY

Customers Also Bought



TE Part #41729-2  
250 FASTON REC 18-16 AWG TPBR



TE Part #F71606-000  
WP-229064-10-9



TE Part #207684-5  
AMPLIMITE,SKT CONT,SZ 22



TE Part #3-1617029-1  
HFW1131K00 = HFW 1/2 SIZE RELA




TE Part #328657  
PIDG R 22-16 COMM 22-18 MIL 2



TE Part #535032-4  
096 EURO TYPE C RECEPT AP ASSY



TE Part #DT15-08PB  
HDR, 8P, BLK, ST, NI/CU, B



TE Part #323696  
SPLICE,SOLIS BUTT HT 12-10



Documents

Product Drawings

SPLICE,SOLIS PARA HT 22-16

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_322326\_F.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_322326\_F.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_322326\_F.3d\_stp.zip

English

3D PDF

English

Customer View Model

ENG\_CVM\_322326\_H1.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_322326\_H1.3d\_stp.zip

English

Customer View Model

ENG\_CVM\_322326\_H1.2d\_dxf.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

STRATO-THERM Terminals & Splices for High Temperature Applications

English

Product Specifications

Application Specification

English

322326

Parallel Splice, 22 – 16 AWG, .3 – 1.42 mm<sup>2</sup> Wire, Serrated, 509 – 3260 CMA, Nickel, Orange, 7.65 mm [.301 in] Length, Loose Piece, Closed Barrel



Instruction Sheets

Instruction Sheet (U.S.)

English

AMP Multiple-Wire Post-Insulated STRATO-THERM Splice Caps

English