

### STRATO-THERM DIAMOND GRIP

TE Internal #: 322823

Butt Splice, 22 – 16 AWG, .26 – 1.65 mm<sup>2</sup> Wire, Serrated, .51 – 3.26 kcmil, 509 – 3260 CMA, Copper, STRATO-THERM DIAMOND GRIP

View on TE.com >



Terminals & Splices > Splices











Splice Type: **Butt Splice**Wire Size: .26 – 1.65 mm²

Sealable: No

Splice Features: Serrated

## **Features**

## **Product Type Features**

Splice Type	Butt Splice
Sealable	No
Compatible With Discrete Wire Type	Stranded
Wire Insulation Support Retention Type	Insulation Support

## **Configuration Features**

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

## **Body Features**

Product Weight	1 g
Splice Features	Serrated

### **Contact Features**

Contact Base Material	Copper
Barrel Type	Closed

### Mechanical Attachment

Wire Insulation Support	With	
-------------------------	------	--



Wire Size	.51 – 3.26 kcmil
Compatible Insulation Diameter Range	3.55 mm[.14 in]
Product Length	22.58 mm[.889 in]
Usage Conditions	
Insulation Option	Uninsulated
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	1000

Loose Piece

## **Product Compliance**

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


## Compatible Parts





# Also in the Series | STRATO-THERM DIAMOND GRIP







# Customers Also Bought






















### **Documents**

## **Product Drawings**

**DIAMOND GRIP 22-16 HR SPLICE** 

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_322823\_F.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_322823\_F.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_322823\_F.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

STRATO-THERM Terminals & Splices for High Temperature Applications

English

## **Product Specifications**

**Application Specification** 

English