

TE Internal #: 328307

Closed End Splice, Serrated, .509 – 3.248 kcmil, 509 – 3248 CMA,

Copper, Red, 12 Serration, 11.3 mm [.445 in] Length, Loose Piece,

Closed Barrel

View on TE.com >



Terminals & Splices > Splices











Splice Type: Closed End Splice

Sealable: No

Splice Features: **Serrated**Wire Size: .509 – 3.248 kcmil

Features

Product Type Features

Splice Type Closed End 9	Splice
Sealable	
Compatible With Discrete Wire Type Solid, Strand	led
Wire Insulation Support Retention Type Non-Insulation	on Support

Configuration Features

Number of Serrations	12
Compatible With Wire & Cable Type	Discrete Wire

Body Features

Insulation Material	Nylon
Insulation Type	Pre-Insulated
Splice Features	Serrated
Primary Product Color	Red

Contact Features

Military Part Class	Class I	
---------------------	---------	--



Contact Base Material	Copper
Barrel Type	Closed
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	.509 – 3.248 kcmil
Terminal Material Thickness	.61 mm[.024 in]
Product Length	11.3 mm[.445 in]
Usage Conditions	
Insulation Option	Fully Insulated
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	Yes
Packaging Features	
Packaging Quantity	1000

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Loose Piece

Product Compliance Disclaimer




This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



TE Part # 47806-2 DIES PIDG 22-16 DIE SET



TE Part # 2392021-2 RED BATTERY DAHT KIT 220V (47689-4)



TE Part # 47386-4 DAHT PG PIDG 26-16 ASSY



TE Part # 58423-1 DIE, RBY IS9252



DAHT PG PIDG 26-16 ASSY



TE Part # 58433-3 PRO CR ASSY, RBY IS9252



TE Part # 59170 T-HEAD PIDG SH 26-14 ASSY



TE Part # 169400 CERTI-LOK FRAME W/O DIES



T-HEAD PIDG 26-14 ASSY







ERGO DIE R.B.Y













Customers Also Bought

















TE Part #333184-000 222K152-25/42-0

TE Part #823211-005 301A011-3-CS-2068-0

Documents

Product Drawings

SPARE WIRE CAP, RED 22-18 AWG

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_328307_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_328307_F.3d_igs.zip

English

Customer View Model

ENG_CVM_328307_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Closed End Splice, Serrated, .509 – 3.248 kcmil, 509 – 3248 CMA, Copper, Red, 12 Serration, 11.3 mm [.445 in] Length, Loose Piece, Closed Barrel



Instruction Sheets

Instruction Sheet (U.S.)

English