




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 1.65 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Electrical Characteristics

Voltage Rating	240 V
----------------	-------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp



Barrel Type

Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Product Length	17 mm[.669 in]
Compatible Insulation Diameter Range	2.01 – 3 mm[.079 – .118 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	.51 – 1.65 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	8000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



KIT

REPRESENTATION ONLY

TE Part # 7-2150365-7
[OCEAN_2.0_SPARE_PART_KIT-090F130F](#)



TE Part # 2150365-1
[OCEAN_2.0_Applicator-E-090F130F-REM](#)



TE Part # 2150365-2
[OCEAN_2.0_Applicator-E-090F130F-REA](#)




TE Part # 1544291-4
[4,8 RECEPTACLE](#)

Also in the Series | **FASTON 250**



[Compression Connectors\(4\)](#)




[Crimp Terminal Housings\(116\)](#)



[Insertion & Extraction Tools\(6\)](#)



[Insulation Boots & Sleeves\(16\)](#)



[Magnet Wire Terminals\(1\)](#)



[PCB Terminals\(134\)](#)




[Quick Disconnects\(421\)](#)



[Splices\(4\)](#)

Customers Also Bought






TE Part #2391865-1
POSITIVE LOCK 250 (6.3 MM) SLEEVE




TE Part #925612-1
STC REC 6.3 Contact SRC Sn



TE Part #2178571-3
STANDARD TIMER HSG 4P



TE Part #160784-3
REC.FOR 2,5 DIA PIN



TE Part #1-282003-1
MONO-SHAPE TAB CONN 3P. ASSY



TE Part #3-1534798-3
AMP DUOPLUG MK2 CONNECTOR
3P SELECTIVE




TE Part #9-1241961-2
STD TIM HOUSING MKII 2POS



TE Part #1862006-5
STD PW TIMER CONTACT



TE Part #336076-3
250 FASTON,E-SPRING REC.,17-14
AWG,PTBR



TE Part #1-282002-5
AMP MONO-SHAPE TAB CONN

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_336075-3_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_336075-3_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_336075-3_L.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

E-Spring Flyer

English

1654742_HOUSEHOLD_APPLIANCES_RAST5

English



Product Specifications

E-SPRING CONTACT

English

Application Specification

English

Instruction Sheets

Instruction Sheet (non U.S.)

English

E-SPRING CONTACT SYSTEM. INSTRUCTIONS FOR MAKING CONNECTION WITH TAB

English

Agency Approvals

Agency Approval Document

English