### Micro-MaTch | Micro-MaTch Industrial

TE Internal #: 338095-8

Wire-to-Board, 8 Position, 1.27 mm [.05 in] Centerline, 2 Row, Plug, Standard Profile, Wire & Cable, Micro-MaTch Industrial, Ribbon

Cable Connectors

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > Ribbon Cable Connectors > Crimp-on-Snap-in Housing



Connector System: Wire-to-Board

Number of Positions: 8

Centerline (Pitch): 1.27 mm [ .05 in ]
Row-to-Row Spacing: 2 mm [ .059 in ]

Number of Rows: 2

All Crimp-on-Snap-in Housing (9)

### **Features**

## **Product Type Features**

Connector Product Type	Housing
Ribbon Cable Connector Header Type	Shrouded
Connector System	Wire-to-Board
Connector & Housing Type	Plug
Connector & Contact Terminates To	Wire & Cable

## **Configuration Features**

Number of Positions	8
Number of Rows	2

### **Electrical Characteristics**

Operating Voltage	100 VDC
Insulation Resistance	1000 ΜΩ

### **Body Features**

Daisy Chain	Without
Primary Product Color	Red
Connector Profile	Standard

#### **Contact Features**



Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material Finish	Matte
Contact Mating Area Plating Material	Tin (Sn)
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin
Contact Type	Socket
Contact Current Rating (Max)	1.5 A
Termination Features	
Termination Method to Wire & Cable	Crimp & Snap
Mechanical Attachment	
Contact Retention Type Within Housing	Snap-In
Mating Alignment	With
PCB Mount Alignment	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Retention Type	Contact Friction
Housing Features	
Housing Material	PBT GF
Centerline (Pitch)	1.27 mm[.05 in]
Dimensions	
PCB Thickness (Recommended)	1.6 mm[.06 in]
Connector Height	12.4 mm[.49 in]
Connector Length	13.5 mm[.531 in]
Row-to-Row Spacing	2 mm[.059 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
Compatible With Agency/Standards Products	UL
UL Rating	Recognized
UL Flammability Rating	UL 94V-0



Compatible With Approved Standards Products	UL E28476
Packaging Features	
Packaging Quantity	500
Packaging Method	Box & Carton

## **Product Compliance**


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts













TE Part # CAT-M5833-C8684A Crimp Contacts - Micro-MaTch



TE Part # 7-100400-8 MICRO-MATCH FSID NP



TE Part # 100400-8 MICRO-MATCH FSID NP





TE Part # 215460-8 MICRO-MATCH FEM.SE



MICRO-MATCH FEM.SE



## Also in the Series | Micro-MaTch Industrial




Board-In Connectors(20)









# Customers Also Bought



















### **Documents**

### **Product Drawings**

MICRO-MATCH COSI HSG.

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_338095-8\_D\_c-338095-8-d.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_338095-8\_D\_c-338095-8-d.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_338095-8\_D\_c-338095-8-d.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

Micro-MaTch Catalog

English

**Ribbon Cable Interconnect Solutions** 

English

Centerline Micro-Match Connector Series

English

### **Product Specifications**

micro-match crimp on snap in male on wire connector

English

**Application Specification** 

English