
34123-2 O NOT USE FOR NEW DESIGN

SOLISTRAND

TE Internal #: 34123-2 Closed Ring Tongue Terminal, 16 AWG, #10 Stud, 5 mm [.197 in] Stud Diameter, Closed Barrel, Straight, Unplated Plating, Uninsulated

View on TE.com >

Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 2050 – 5180 CMA

Stud Size: **#10**

Features

Product Type Features

Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#10
Sealable	No
Wire Insulation Support Retention Type	Non-Insulation Support
Configuration Features	
Number of Holes	1
Contact Features	
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Unplated
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	2050 – 5180 CMA
Stud Diameter	5 mm[.197 in]



34123-2

Closed Ring Tongue Terminal, 16 AWG, #10 Stud, 5 mm [.197 in] Stud Diameter, Closed Barrel, Straight, Unplated Plating, Uninsulated



Tongue Thickness	.79 mm[.031 in]
Product Length	16.15 mm[.636 in]
Barrel Inside Diameter	2.16 mm[.085 in]
Usage Conditions	
Insulation Option	Uninsulated
Operation/Application	
Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Quantity	1000
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU

Compliant

EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on

34123-2

Closed Ring Tongue Terminal, 16 AWG, #10 Stud, 5 mm [.197 in] Stud Diameter, Closed Barrel, Straight, Unplated Plating, Uninsulated





requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Customers Also Bought





TE Part #797339M011TE Part #E807NTFR-1-1/2-0-SP-CS5445TERMINAL LUBRICANT

Documents

Product Drawings SOLIS,RING,16-14,10,UNPLTD

English

34123-2

Closed Ring Tongue Terminal, 16 AWG, #10 Stud, 5 mm [.197 in] Stud Diameter, Closed Barrel, Straight, Unplated Plating, Uninsulated



CAD Files

3D PDF

English

Customer View Model

ENG_CVM_34123-2_G.2d_dxf.zip

English

Customer View Model

ENG_CVM_34123-2_G.3d_igs.zip

English

Customer View Model

ENG_CVM_34123-2_G.3d_stp.zip

English

3D PDF

3D

Customer View Model ENG_CVM_CVM_34123-2_S.2d_dxf.zip

English

Customer View Model ENG_CVM_CVM_34123-2_S.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_34123-2_S.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms**

Datasheets & Catalog Pages SOLISTRAND - QRG

English

Instruction Sheets Instruction Sheet (U.S.)

English