




Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Header**

PCB Mount Orientation: **Vertical**

Connector System: **Wire-to-Board**

Number of Positions: **4**

Number of Rows: **1**

Features

Product Type Features

Mixed & Hybrid Header	No
Connector Shape	Rectangular
PCB Connector Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Columns	4
Number of Loaded Positions	4
Number of Power Positions	4
Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Vertical
Number of Positions	4



Number of Rows	1
----------------	---

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.27 – 1.79 µm[50 – 70 µin]
Contact Size	2.95mm
Contact Mating Area Plating Material Thickness	3.81 – 5.08 µm[150 – 200 µin]
PCB Contact Termination Area Plating Material Thickness	3.81 – 5.08 µm[150 – 200 µin]
Contact Shape & Form	Round
Contact Layout	Inline
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Pre-Tin
Contact Mating Area Plating Material	Pre-Tin
Contact Type	Socket
Contact Current Rating (Max)	12 A

Termination Features

Termination Post & Tail Diameter	1.57 mm[.062 in]
Termination Post & Tail Length	3.56 mm[.14 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Panel Mount Feature	Without
Mating Retention Type	Locking Tab
Mating Retention	With
Mating Alignment Type	Polarization
PCB Mount Retention	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount
Mating Alignment	With

Housing Features



Mating Entry Location	Top
Housing Material	Nylon
Centerline (Pitch)	6.35 mm[.25 in]

Dimensions

Connector Width	7.62 mm[.3 in]
PCB Thickness (Recommended)	1.57 mm[.062 in]
Connector Height	13.97 mm[.55 in]
Connector Length	26.67 mm[1.05 in]
Profile Height from PCB	14.73 mm[.58 in]

Usage Conditions

Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]

Operation/Application

Shielded	No
Circuit Application	Power

Industry Standards

Compatible With Agency/Standards Products	CSA, UL, VDE
UL Rating	Recognized
Compatible With Approved Standards Products	UL E28476
Glow Wire Rating	Standard Part - Not Glow Wire
UL Flammability Rating	UL 94V-2

Packaging Features

Packaging Quantity	100
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247)



Candidate List Declared Against: JAN 2025
(247)
Does not contain REACH SVHC

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
-----------------	---

Solder Process CapabilityWave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 641776-1
04P UMNL STR/REL

TE Part # 1586845-1
04P UMNL CAP HSG NATL, GW

TE Part # 926305-1
4P UNIV M-N-L CAP

TE Part # 794707-1
04P UMNL CAP HSG,BLACK

TE Part # 1-480702-0
04P UMNL PLUG HSG NATL

TE Part # 350811-1
STR/REL CLAMP

TE Part # 350848-4
04P UMNL PLUG TEST ASSY 94VO

TE Part # 794274-1
04P UMNL WIRE SEAL



TE Part # 6-641968-1
4P UMNL PIN HDR ASS POL VO BLU

TE Part # 770351-1
04P UMNL PIN HDR ASSY W/O DRNS

TE Part # 641776-2
04P UMNL STR/REL

TE Part # 641968-3
04P UMNL PIN HDR ASSY POL 94VO

TE Part # 794273-1
04P UMNL INTERFACE SEAL

TE Part # 926305-6
UNML4WAY CAP

TE Part # 641968-4
4P UMNL PIN HDR POL VO, AU, LF

TE Part # 1-350589-0
STR/REL CLAMP NATL

TE Part # 1586872-1
04P UMNL HDR ASSY, GW

TE Part # 641775-2
04P UMNL STR/REL NATL

TE Part # 641775-1
04P UMNL STR/REL & INSRT NATL

Also in the Series | Universal MATE-N-LOK

Circular Power Connectors(2)

Connector Contacts(208)

Connector Hardware(12)

Power Contacts(208)

Rectangular Power Connectors(651)

Standard Circular Connectors(1)


Customers Also Bought



TE Part #2176163-3
06P 10R 0.1% 5PPM 10K




TE Part #350827-1
06P UMNL HDR ASSY PC 94VO



TE Part #1879657-1
H4 10R 0.1% 15PPM



TE Part #640467-1
05P UMNL HDR ASSY



TE Part #350763-4
09P UMNL HDR ASSY PC



TE Part #350764-4
12P UMNL HDR ASSY PC




TE Part #175178-1
PL EX 250 REC TERMINAL-FLAG 12-10 PTPB



TE Part #2-2172067-2
M8 MALE R/A PNL.3P.PCB (AU)



TE Part #350765-4
15P UMNL HDR ASSY PC



TE Part #167892-3
8 POS LINKING TERM W ACT. PIN

Documents

Product Drawings

04P UMNL HDR ASSY PC

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_350761-4_T.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_350761-4_T.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_350761-4_T.3d_stp.zip

English

3D PDF

English



Customer View Model

[ENG_CVM_350761-4_N.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_350761-4_N.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_350761-4_N.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY](#)

English

Product Specifications

[Application Specification](#)

English

Instruction Sheets

[Instruction Sheet \(U.S.\)](#)

English

Agency Approvals

[VDE Certificate](#)

English

[VDE Certificate](#)

English