

#### **SOLISTRAND**

TE Internal #: 35187

Parallel Splice, 2 AWG, 34 – 35 mm<sup>2</sup> Wire, Serrated, 52600 – 83700 CMA, Copper, 16.26 mm [.64 in] Length, Loose Piece, Closed Barrel

View on TE.com >



Terminals & Splices > Splices











Splice Type: Parallel Splice

Wire Size: 34 – 35 mm<sup>2</sup>

Sealable: No

Splice Features: Serrated

## **Features**

## **Product Type Features**

Splice Accessory Type	Splice
Splice Type	Parallel Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support

## **Configuration Features**

Compatible With Wire & Cable Type	Discrete Wire

## **Body Features**

Product Weight	11.416 g
Splice Features	Serrated

## **Contact Features**

	100 μin
Terminal Plating Material	Tin
Contact Base Material	Copper
Barrel Type	Closed



## Mechanical Attachment

Wire Insulation Support	Without
Dimensions	
Outside Diameter	13.7 mm[.539 in]
Wire Size	52600 – 83700 CMA
Barrel Inside Diameter	9.39 mm[.37 in]
Terminal Material Thickness	1.85 mm[.073 in]
Product Length	16.26 mm[.64 in]
Usage Conditions	
Insulation Option	Uninsulated
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	50
Packaging Method	Loose Piece

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

## Compatible Parts



TE Part # 1490414-2 HYP10 SOLIS HD 6-4AWG INDENTER



HYP8 SOLIS 6-2AWG INDENTER











## Customers Also Bought

























## **Documents**

# Product Drawings SPLICE, SOLIS PARA 2

English

## **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_35187\_V.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_35187\_V.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_35187\_V.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

#### **Instruction Sheets**

Instruction Sheet (U.S.)

English

## **Agency Approvals**

UL

English