




Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Header**

PCB Mount Orientation: **Vertical**

Connector System: **Board-to-Board**

Number of Positions: **50**

Number of Rows: **2**

Features

Product Type Features

PCB Connector Type	PCB Mount Header
Connector System	Board-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Columns	25
Number of Loaded Positions	50
Stacking Configuration	Stack Through
Connector Contact Load Condition	Fully Loaded
Stackable	Yes
PCB Mount Orientation	Vertical
Number of Positions	50



Number of Rows	2
----------------	---

Electrical Characteristics

Impedance	100 Ω
Insulation Resistance	10000 MΩ
Dielectric Withstanding Voltage (Max)	500 Vrms

Signal Characteristics

Data Rate	25 Gb/s
-----------	---------

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Contact Shape & Form	Rectangular
PCB Contact Termination Area Plating Material Thickness	4 – 6 μm[157.48 – 236.22 μin]
Contact Layout	Matrix
Contact Mating Area Length	2.9 mm[.114 in]
Contact Base Material	Copper Alloy
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Pin
Contact Current Rating (Max)	1 A

Termination Features

Termination Method to PCB	Surface Mount
---------------------------	---------------

Mechanical Attachment

Mounting Alignment Feature Length	.65 mm[.025 in]
Mating Alignment Type	Blindmate
PCB Mount Alignment Type	Locating Posts
PCB Mount Retention	Without
PCB Mount Alignment	With
Connector Mounting Type	Board Mount
Mating Alignment	With

Housing Features

Mating Entry Location	Top
Housing Material	LCP



Centerline (Pitch)	1 mm[.039 in]
--------------------	---------------

Dimensions

Row-to-Row Spacing	1.5 mm[.059 in]
Stack Height	2 mm[.079 in]
Connector Width	6.75 mm[.266 in]
Connector Height	5.8 mm[.228 in]
Connector Length	28.95 mm[1.139 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Assembly Process Feature	Pick and Place Cover
Shielded	No
Circuit Application	Power, Signal & High Speed Data

Industry Standards

Compatible With Agency/Standards Products	DIN, UL
Industry Standard	IEC
Compatible With Approved Standards Products	UL
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Reel Diameter	330 mm[12.99 in]
Packaging Quantity	400
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC









Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 354176-E MSPEED 50 F SMD F6 B AB VV 137 094 ** E	 TE Part # 354178-E MSPEED 50 F SMD F8 B AB VV 137 094 ** E	 TE Part # 354188-E MSPEED 50 M SMDTHR M10 B AB VV 137 094 *	 TE Part # 254876-E MSPEED 50 F SMD F4 B AB VV 137 094 ** E
 TE Part # 354175-E MSPEED 50 F SMDTHR F4 B AB VV 137 094 *	 TE Part # 354177-E MSPEED 50 F SMDTHR F6 B AB VV 137 094 *	 TE Part # 354181-E MSPEED 50 F SMDTHR F10 B AB VV 137 094 *	 TE Part # 354179-E MSPEED 50 F SMDTHR F8 B AB VV 137 094 *
 TE Part # 354180-E MSPEED 50 F SMD F10 B AB VV 137 094 **	 TE Part # 354186-E MSPEED 50 M SMDTHR M9 B AB VV 137 094 *		

Also in the Series | ERNI MicroSpeed



Board-to-Board Headers & Receptacles(68)



PCB Headers & Receptacles(76)



Rectangular Power Connectors(51)



Wire-to-Board Headers & Receptacles (8)

Customers Also Bought



TE Part #374954-E
MSPPM 5 F THR F4 B A V 137 094 * E008 J




TE Part #2336313-2
QSFP 25GIG 32AWG 1 METER




TE Part #1571983-8
GDH06S04=DIP SWITCH



TE Part #374722-E
MSPEED 50 M SMDTHR * 90BE AB VV 137 094



TE Part #374955-E
MSPPM 5 M THR M1 B A V 137 094 * E008 J



TE Part #281739-5
HEADER HE14 STRAIGHT 2X5 P



TE Part #5177986-8
0.8FH,P05H.5,160,08/Sn,TR,SC



TE Part #5177986-1
0.8FH,P05H.5,040,08/Sn,TR,SC



TE Part #9-215464-0
20P.MICRO-MATCH MOB



TE Part #1571983-1
GDH02S04=DIP SWITCH

Documents

CAD Files

Customer View Model

[ENG_CVM_CVM_354183-E_1.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_354183-E_1.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_CVM_354183-E_1.2d_dxf.zip](#)

354183-E

PCB Mount Header, Vertical, Board-to-Board, 50 Position, 1 mm [.039 in] Centerline, Fully Shrouded, Gold (Au), Surface Mount, ERNI MicroSpeed



English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.