PRD-11DH0-12 ACTIVE

TE Internal #: 4-1393127-7 General Purpose Power Relay, DC, Monostable, 2 Form C DPDT-CO, 20 A Contact Rating, 12 VDC Coil Voltage, 600 VAC Contact Voltage

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: General Purpose Power Relay

Current Type: DC

Coil Magnetic System: Monostable

Contact Arrangement: 2 Form C DPDT-CO

Contact Current Rating: 20 A

Features

Product Type Features

I U U	uct.		

Relay & Contactor Type	General Purpose Power Relay	
Configuration Features		
Coil Special Features	UL Coil Insulation Class B	
Contact Number of Poles	2	
Contact Arrangement	2 Form C DPDT-CO	
Electrical Characteristics		
Contact Switching Load (Min)	1A @ 12V	
Coil Resistance	71 Ω	
Contact Switching Voltage (Max)	600 VAC	
Contact Current Rating	20 A	
Coil Voltage Rating	12 VDC	
Contact Voltage Rating	125 VDC	
Coil Power Rating DC	2 W	
Insulation Initial Dielectric Between Contacts & Coil	2000 Vrms	

PRD-11DH0-12

General Purpose Power Relay, DC, Monostable, 2 Form C DPDT-CO, 20 A Contact Rating, 12 VDC Coil Voltage, 600 VAC Contact Voltage



Contact Material	Ag
Termination Features	
Main Termination & Connection Type	8-32 Screw
Coil Termination & Connection Type	6-32 Screw
Mechanical Attachment	
Product Mounting Feature Type	Mounting Hole
Product Mount Type	Panel Mount
Dimensions	
Product Width	63.8 mm[2.51 in]
Product Length	85.73 mm[3.37 in]
Product Height	63.5 mm[2.5 in]
Usage Conditions	
Operating Temperature Range	-55 – 80 °C[-67 – 176 °F]
Environmental Ambient Temperature (Max)	80 °C[176 °F]

Current Type

DC

Coil Magnetic System	Monostable
Packaging Features	
Packaging Method	Tray
Other	
Contact Current Class	20 – 30 A
Coil Power Rating Class	1.5 – 2 W
Product Compliance	
	Compliant with Exemptions
Product Compliance For compliance documentation, visit the product page on TE.com>	Compliant with Exemptions Not Compliant
Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	

PRD-11DH0-12

General Purpose Power Relay, DC, Monostable, 2 Form C DPDT-CO, 20 A Contact Rating, 12 VDC Coil Voltage, 600 VAC Contact Voltage



SVHC > Threshold: Cd (7.5% in Component Part) DBMC (.5% in 20635946948) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your

geographic location.

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Halogen Content

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



PRD-11DH0-12

General Purpose Power Relay, DC, Monostable, 2 Form C DPDT-CO, 20 A Contact Rating, 12 VDC Coil Voltage, 600 VAC Contact Voltage







Documents

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_4-1393127-7_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_4-1393127-7_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_4-1393127-7_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages PRD 10 to 50 Amp Heavy Duty AC or DC Power Relay

English

Product Specifications

Definitions General Purpose Relays

English

Agency Approvals UL

English