4-1761184-1 ACTIVE

AMPLIMITE

TE Internal #: 4-1761184-1

Plug, Flat Ribbon Cable, 24 AWG, .2 mm² / .205 mm² Wire, Cableto-Board, 4 Position, 1.27 mm [.05 in] Centerline, Wire & Cable,

Signal, SDL Connectors

View on TE.com >



Connectors > Audio & Video Connectors > SDL Connectors











Connector & Housing Type: Plug

Compatible With Wire & Cable Type: Flat Ribbon Cable

Wire Size: 24 AWG

Connector System: Cable-to-Board

Features

Product Type Features

Receptacle Configuration	Standard
Connector & Housing Type	Plug
Connector System	Cable-to-Board
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Compatible With Wire & Cable Type	Flat Ribbon Cable
Number of Positions	4

Body Features

Shield Plating Material	Tin over Nickel
Shield Material	Brass

Contact Features

Contact Mating Area Plating Material	Gold (Au)
Contact Base Material	Copper Alloy
	50 μin



Contact Current Rating (Max)	1.5 A
------------------------------	-------

Mechanical Attachment

Polarization Code	D
PCB Mount Retention	Without
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Color	Smoke Gray
Housing Material	Polycarbonate GF
Centerline (Pitch)	1.27 mm[.05 in]

Dimensions

Conductor Insulation Diameter Range	1.27 mm[.05 in]
Wire Size	24 AWG

Usage Conditions

Operating Temperature Range	-20 - 80 °C[-4 - 176 °F]

Operation/Application

Circuit Application Signal

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products



will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought















Documents

Product Drawings
4 SDL FLAT PLUG ASSY

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_4-1761184-1_A.2d_dxf.zip

Plug, Flat Ribbon Cable, 24 AWG, .2 mm² / .205 mm² Wire, Cable-to-Board, 4 Position, 1.27 mm [.05 in] Centerline, Wire & Cable, Signal, SDL Connectors



English

Customer View Model

ENG_CVM_CVM_4-1761184-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_4-1761184-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL Report

English