

4-1904124-3 ✓ ACTIVE



Micro Relay A

TE Internal #: 4-1904124-3

General Purpose Power Relay, DC, Monostable, 1 Form C SPDT-CO, 30 A Contact Rating, 12 VDC Coil Voltage, 12 VDC Contact Voltage, Micro Relay A

[View on TE.com >](#)

Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: **General Purpose Power Relay**

Current Type: **DC**

Coil Magnetic System: **Monostable**

Contact Arrangement: **1 Form C SPDT-CO**

Contact Current Rating: **30 A**

Features

Product Type Features

Relay & Contactor Type	General Purpose Power Relay
------------------------	-----------------------------

Configuration Features

Contact Arrangement	1 Form C SPDT-CO
---------------------	------------------

Electrical Characteristics

Contact Switching Load (Min)	1000mA @ 5VDC
Contact Limiting Short-Time Current	150 A
Contact Limiting Making Current	120 A
Coil Resistance	119 Ω
Contact Limiting Continuous Current	30 A
Contact Limiting Breaking Current	30 A
Insulation Initial Dielectric Between Open Contacts	500 Vrms
Contact Current Rating	30 A
Coil Voltage Rating	12 VDC
Contact Voltage Rating	12 VDC
Coil Power Rating DC	1.2 W
Insulation Initial Dielectric Between Contacts & Coil	500 Vrms

Body Features



Product Weight	16 g[.565 oz]
----------------	---------------

Enclosure Type	Dust Protected
----------------	----------------

Contact Features

Contact Material	Silver Alloy
------------------	--------------

Termination Features

Main Termination & Connection Type	Quick Connect Terminals
------------------------------------	-------------------------

Coil Termination & Connection Type	Quick Connect Terminals
------------------------------------	-------------------------

Mechanical Attachment

Product Mount Type	Socket Mount
--------------------	--------------

Dimensions

Product Width	15.5 mm[.61 in]
---------------	-----------------

Product Length	23 mm[.906 in]
----------------	----------------

Product Height	25.4 mm[1 in]
----------------	---------------

Usage Conditions

Environmental Category of Protection	RTI
--------------------------------------	-----

Environmental Ambient Temperature (Max)	125 °C[257 °F]
---	----------------

Operation/Application

Current Type	DC
--------------	----

Coil Magnetic System	Monostable
----------------------	------------

Other

Contact Current Class	20 – 30 A
-----------------------	-----------

Coil Power Rating Class	1 – 1.5 W
-------------------------	-----------

Environmental Ambient Temperature Class	105 – 125 °C
---	--------------

Height Class (Mechanical)	25 – 30 mm
---------------------------	------------

Length Class (Mechanical)	20 – 25 mm
---------------------------	------------

Width Class (Mechanical)	12 – 16 mm
--------------------------	------------

Product Compliance

For compliance documentation, visit the product page on [TE.com](https://www.te.com)>

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------

EU ELV Directive 2000/53/EC	Compliant
-----------------------------	-----------

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
---	---



EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JAN 2025 (247)

Candidate List Declared Against: JAN 2024 (240)

Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Also in the Series | Micro Relay A



Customers Also Bought



TE Part #2112045-3
SLIDE, FOR 26POS TAB HSG



TE Part #1-1823034-1
MCON 9.5, 16SQMM ASSY 0,8MM
TAB



TE Part #280919-4
FF 187 REC 0.5-1.5MM2 TPPB
TAB



TE Part #K1127520
Battery Disconnect 35-213-151-R-900



TE Part #925544-2
FF 110 REC 0.5-1.5MM2 PB LP




TE Part #1-1904045-5
V23333Z1001B045-EV-100



TE Part #K1070513
Schlagschalter (Hauptantr) 06-63-410



TE Part #1825027-1
FSMRA1JHL04=R/A, TACT PB SW, 100



TE Part #1393310-2
VCFM-1000=FROM SEC



TE Part #964595-1
HALTER F2XSICHERG E

Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_4-1904124-3_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_4-1904124-3_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_4-1904124-3_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Automotive Relay Application Notes

English

Micro Relay A, Micro ISO, Plug-in

English



Product Specifications

Definitions General Purpose Relays

English