



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **2.1 – 3.31 mm<sup>2</sup>**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

|                 |        |
|-----------------|--------|
| Insertion Force | Normal |
|-----------------|--------|

Configuration Features

|                                   |               |
|-----------------------------------|---------------|
| Compatible With Wire & Cable Type | Discrete Wire |
| Connection Capacity               | Single        |

Contact Features

|                                |                 |
|--------------------------------|-----------------|
| Quick Disconnect Terminal Type | Receptacle      |
| Mating Tab Width               | 6.35 mm[.25 in] |
| Mating Tab Thickness           | .81 mm[.032 in] |
| Terminal Orientation           | Straight        |
| Contact Base Material          | Brass           |
| Terminal Plating Material      | Tin             |
| Crimp Type                     | F-Crimp         |
| Barrel Type                    | Open            |

Termination Features

|                       |              |
|-----------------------|--------------|
| Product Terminates To | Wire & Cable |
|-----------------------|--------------|



Mechanical Attachment

|                         |        |
|-------------------------|--------|
| Wire Insulation Support | With   |
| Mating Retention Type   | Dimple |

Dimensions

|                                      |                  |
|--------------------------------------|------------------|
| Product Length                       | 20.7 mm[.815 in] |
| Compatible Insulation Diameter Range | 4.06 mm[.16 in]  |
| Terminal Material Thickness          | .46 mm[.018 in]  |
| Wire Size                            | 2.1 – 3.31 mm²   |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Insulation Option           | Uninsulated                |
| Operating Temperature Range | -40 – 110 °C[-40 – 230 °F] |

Industry Standards

|                                           |         |
|-------------------------------------------|---------|
| Compatible With Agency/Standards Products | CSA, UL |
|-------------------------------------------|---------|

Packaging Features

|                    |                    |
|--------------------|--------------------|
| Packaging Quantity | 500                |
| Packaging Method   | Loose Piece/Carton |

Other

|      |         |
|------|---------|
| Line | Premier |
|------|---------|

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                     |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                     |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                       |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2025 (247)<br>Candidate List Declared Against: JAN 2025 (247)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                           |
| Solder Process Capability                     | Not applicable for solder process capability                                                                                  |

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts

|                                                            |                                                                   |                                                                             |                                                           |
|------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------------------------|
| <p>TE Part # 61873-1<br/>250 FASTON REC 18-14 AWG TPBR</p> | <p>TE Part # 58525-1<br/>PROCRIMPER TOOL &amp; DIE</p>            | <p>TE Part # 8-61765-1<br/>FASTON, ADAPTER 250 HOUSING REC&amp;TAB TPBR</p> | <p>TE Part # 90120<br/>DAHT 250 FASTON REC 14-10 ASSY</p> |
| <p>TE Part # 58525-2<br/>PROCRIMPER DIE</p>                | <p>TE Part # 61810-2<br/>FASTON .250 (6.3 MM) RECEPTACLE TPBR</p> |                                                                             |                                                           |

Also in the Series | FASTON 250

|                                  |                                     |                                            |                                           |
|----------------------------------|-------------------------------------|--------------------------------------------|-------------------------------------------|
| <p>Compression Connectors(4)</p> | <p>Crimp Terminal Housings(116)</p> | <p>Insertion &amp; Extraction Tools(6)</p> | <p>Insulation Boots &amp; Sleeves(16)</p> |
|----------------------------------|-------------------------------------|--------------------------------------------|-------------------------------------------|





Magnet Wire Terminals(1)



PCB Terminals(134)



Quick Disconnects(421)




Splices(4)

Customers Also Bought




TE Part #CN21  
CAP NUT, CONDUIT ADAPTER, NW22




TE Part #2-1879664-5  
H8 2K05 0.1% 15PPM



TE Part #66262-4  
MALE CONTACT ASSY. (L.P.)



TE Part #640551-4  
04P MTA156 COVER




TE Part #608803-1  
CABLE TIE MOUNT, 4-WAY, 1-1/8"




TE Part #1-1337431-0  
BNC Str Plg Hex 75Ohm Nickel Pltd  
RG179B



TE Part #1-1337552-0  
FME Str Jk Hex Nickel Pltd RG58C/U,  
141A



TE Part #62428-2  
250 FASTON REC 12-10 AWG TPBR



TE Part #643493-4  
04P MTA156 HDR ASSY STR W/O#3



TE Part #1-100103-4  
14P.A/L.STRAIN REL.

Documents

Product Drawings

250 FASTON REC 14-12 AWG TPBR

English

CAD Files

Customer View Model

ENG\_CVM\_CVM\_41829-1\_AN.2d\_dxf.zip

English

3D PDF



3D

Customer View Model

[ENG\\_CVM\\_CVM\\_41829-1\\_AN.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_41829-1\\_AN.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Wire Preparation And Crimp Inspection Guide](#)

English

Agency Approvals

[UL Report](#)

English