




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **.32 – .82 mm²**

Mating Tab Width: **4.75 mm [.187 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Product Length	17.14 mm[.675 in]
Compatible Insulation Diameter Range	2.03 – 3.05 mm[.08 – .12 in]
Terminal Material Thickness	.51 mm[.02 in]
Wire Size	.32 – .82 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	5000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts


 TE Part # 2836284-2 OCEAN_2.0_Applicator-S-090F155O-RSA	 KIT TE Part # 7-2836284-7 OCEAN_2.0_SPARE_PART_KIT-090F155O	 TE Part # 1217118-1 110 FASTON,TAB,20-16 AWG,PTBR	 TE Part # 1217891-1 187 FASTON,TAB,TPBR
 TE Part # 2836284-1 OCEAN_2.0_Applicator-S-090F155O-RSM	 TE Part # 1742753-1 FASTON 2MM TAB 18-22AWG TPBR	 TE Part # 2305570-1 Strip Terminal Cutter-Side Feed-No Crimp	

Also in the Series | FASTON 187

 Crimp Terminal Housings(40)	 Insertion & Extraction Tools(1)	 Insulation Boots & Sleeves(1)	 Joints & Splices(1)
 PCB Terminals(42)	 Quick Disconnects(205)	 Splices(1)	

Customers Also Bought





TE Part #42475-4
250 FASTON TAB 22-18 AWG TPBR



TE Part #42617-2
187 FASTON REC 20-16 AWG TPBR



TE Part #4-1803000-8
ANVIL



TE Part #184030-1
RECPT, CONTACT 070, AUPHBZ



TE Part #2-1633730-4
CRIMPER, WIRE F .062 F



TE Part #3-2119582-7
CRIMPER,INSULATION F PREMIUM




TE Part #102398-7
18 AMPMODU MT ASSY DR .100CL



TE Part #130106
TERM, RT, SOLIS, 16-14, M5



TE Part #174777-1
PL 110 REC 20-16 AWG 0.25 X 10.4 PTBR



TE Part #776127-2
2POS .070 MULTILOCK PLUG RIGHT

Documents

Product Drawings

187 FASTON TAB 22-18 AWG TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_42490-3_AT.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_42490-3_AT.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_42490-3_AT.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



FASTON Tabs

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English