

Potter & Brumfield

TE Internal #: 5-1393028-1

DC Input Solid State Relay, 1 Form A SPST-NO, 3 – 8 VDC Input, 3

– 60 VDC Output, DC Output, Board Mount, Red

View on TE.com >




Relays & Contactors > Solid State Relays











Input Current Type: DC

Contact Arrangement: 1 Form A SPST-NO

Input Voltage: 3-8 VDC

Output Voltage Rating: 3 – 60 VDC

Output Switching: Zero

Features

Configuration Features

Contact Arrangement	1 Form A SPST-NO
Electrical Characteristics	
Insulation Initial Dielectric Between Contacts & Coil	4000 Vrms
Input Voltage	3 – 8 VDC
Output Voltage Rating	3 – 60 VDC
Body Features	
Primary Product Color	Red
Product Weight	22.1 g[.87 oz]
Termination Features	
Relay Connection Type	PCB Termination
Terminal Configuration	Solder Pins
Mechanical Attachment	

Board Mount

Product Mount Type



Product Length	43.5 mm[1.71 in]
Product Width	10.3 mm[.405 in]
Product Height	25.5 mm[1 in]
Usage Conditions	
Operating Temperature Range	-30 – 80 °C[-22 – 176 °F]
Operation/Application	
Input Current Type	DC
Output Switching	Zero
Output Current Type	DC

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Pb (88% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts



Customers Also Bought



















TE Part #2-1617529-8 D703008=0200 J RELAY

Documents

CAD Files

Customer View Model ENG_CVM_CVM_5-1393028-1_C1.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_5-1393028-1_C1.3d_stp.zip

English

DC Input Solid State Relay, 1 Form A SPST-NO, 3-8 VDC Input, 3-60 VDC Output, DC Output, Board Mount, Red



Customer View Model

ENG_CVM_CVM_5-1393028-1_C1.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

ODCM_Datasheet

English

Agency Approvals

UL

English