


SCHRACK | SCHRACK Power PCB Relay RT1

TE Internal #: 5-1393240-6 General Purpose Power Relay, AC, Monostable, 1 Form A SPST-NO, 16 A Contact Rating, 230 VAC Coil Voltage, SCHRACK Power PCB Relay RT1

View on TE.com >

Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: General Purpose Power Relay

Current Type: AC

Coil Magnetic System: Monostable

Contact Arrangement: 1 Form A SPST-NO

Contact Current Rating: 16 A

Features

Connectivity

Product Type Features

Relay & Contactor Type	General Purpose Power Relay
Configuration Features	
Contact Number of Poles	1
Coil Special Features	UL Coil Insulation Class F
Contact Arrangement	1 Form A SPST-NO
Electrical Characteristics	
Contact Limiting Making Current	30 A
Contact Limiting Continuous Current	16 A
Insulation Initial Dielectric Between Open Contacts	1000 Vrms
Contact Switching Voltage (Max)	400 VAC
Coil Resistance	32500 Ω
Coil Power Rating AC	.75 VA
Contact Current Rating	16 A
Coil Voltage Rating	230 VAC

General Purpose Power Relay, AC, Monostable, 1 Form A SPST-NO, 16 A Contact Rating, 230 VAC Coil Voltage, SCHRACK Power PCB Relay RT1



Contact Voltage Rating	250 VAC
Insulation Initial Dielectric Between Contacts & Coil	5000 Vrms
Body Features	
Product Weight	14 g[.494 oz]
Enclosure Type	Flux Resistant Automatic Solder Capable
Contact Features	
Contact Material	AgNi90/10
Termination Features	
Main Termination & Connection Type	Solder Pins
Coil Termination & Connection Type	Solder Pins
Mechanical Attachment	
Product Mount Type	Board Mount
Dimensions	
Insulation Clearance Between Contact & Coil	10 mm[.394 in]
Insulation Creepage Between Contact & Coil	10 mm[.394 in]
Product Width	12.7 mm[.5 in]
Product Length	29 mm[1.14 in]
Product Height	15.7 mm[.618 in]
Usage Conditions	
Operating Temperature Range	-40 – 70 °C[-40 – 158 °F]
Environmental Category of Protection	RTII
Environmental Ambient Temperature (Max)	70 °C[158 °F]
Operation/Application	
Solder Process	Wave Solder Capable
Current Type	AC
Coil Magnetic System	Monostable
Packaging Features	
Packaging Method	Carton
Other	
Contact Current Class	16 A
Height Class (Mechanical)	15 – 16 mm

General Purpose Power Relay, AC, Monostable, 1 Form A SPST-NO, 16 A Contact Rating, 230 VAC Coil Voltage, SCHRACK Power PCB Relay RT1



Length Class (Mechanical)	25 – 30 mm
Width Class (Mechanical)	12 – 16 mm
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




General Purpose Power Relay, AC, Monostable, 1 Form A SPST-NO, 16 A Contact Rating, 230 VAC Coil Voltage, SCHRACK Power PCB Relay RT1





Also in the Series | SCHRACK Power PCB Relay RT1






General Purpose Power Relays(190)



Customers Also Bought



General Purpose Power Relay, AC, Monostable, 1 Form A SPST-NO, 16 A Contact Rating, 230 VAC Coil Voltage, SCHRACK Power PCB Relay RT1





Documents

CAD Files

Customer View Model

ENG_CVM_CVM_5-1393240-6_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-1393240-6_F.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_5-1393240-6_F.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the Terms and Conditions of use

Datasheets & Catalog Pages

Power PCB Relay RT1

English

Product Specifications Definitions General Purpose Relays

English

Agency Approvals **VDE** Certificate

English