



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **642 – 1021 CMA**

Mating Tab Width: **2.8 mm [.11 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------



Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple
Extraction Force	6.1 kgf

Dimensions

Product Length	14 mm[.55 in]
Compatible Insulation Diameter Range	1.3 – 2 mm[.051 – .078 in]
Terminal Material Thickness	.25 mm[.01 in]
Wire Size	642 – 1021 CMA

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	500
Packaging Method	Loose Piece/Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 160668-2
110 FASTIN FASTON,REC.,20-16 AWG, PTBR

TE Part # 141628-4
110 FASTON HSG.,REC.,1 POS, BLACK

TE Part # 141628-2
110 FASTON HSG.,REC.,1 POS, NATURAL

TE Part # 574868
DAHT TAPER PIN FASTON 24-22 ASSY

TE Part # 734520-1
.110 FAST.HANDTOOL

Also in the Series | FASTON 110

Crimp Terminal Housings(13)

Insertion & Extraction Tools(1)

PCB Terminals(22)

Quick Disconnects(164)


Customers Also Bought



TE Part #T4112012051-000
M12 F, 5P GOLD A_CODE RA
SHIELDED PG9



TE Part #T4113012051-000
M12 M, 5P GOLD A_CODE RA
SHIELDED PG9



TE Part #1-480417-0
110 FASTON HSG.,REC.,1 POS,
NATURAL



TE Part #205042-1
12 PC. BLOCK



TE Part #962905-1
TAB AS 4.8x0.8 CONTACT CS SWS Sn



TE Part #825457-6
MOD 2 PINHDR 2X06P.



TE Part #364175-E
M12 FEMALE, D CODE, 4P, 17MM
SMT



TE Part #61624-1
RING CRIMP 16-12 AWG BR



TE Part #1-1106102-1
F-STI-M3



TE Part #1544291-1
4,8 RECEPTACLE

Documents

Product Drawings

FASTON 110 REC 22-20 AWG ELECTRO TPBR

English

CAD Files

Customer View Model

ENG_CVM_CVM_5-160321-2_K.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-160321-2_K.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-160321-2_K.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Agency Approvals



UL Report

English